

HD175-M57-A (KIT)

Kit Contents:

- 1. Hardware (Screws, "L" Brackets, Metal Strap)
- 2. Rubber Boot for Cap.
- 3. Instructions



Ballast Type:	Magnetic	Starting Method:	Regular Start
Lamp Type:	Metal Halide	Input Voltage:	120/277/347
Input Frequency:	60Hz	Recommended Fuse:	5/2/2
ANSI Code:	M57/M107	Rated Lamp Watts:	175/150W
Circuit Type:	CWA	Insulation Class:	H (180°C)
Power Factor:	0.90	Input Watts:	210W
Open Circuit Volts:	300-350V	Min Start Temp (°F/°C):	-20/-30
Nom. Open Circuit Voltage:	350V	Warranty:	Two Years

ELECTRICAL SPECIFICATIONS

Input	Input Current (Amps)			Input Volts at	UL1029 Coil Temp.	Regu	lation	Short Circ	uit Cu	rrent
Volts	Operating	Open Circuit	Starting	Lamp Dropout	Code	Line Volts	Lamp Watt	Secondary Current	Input Current	
120	1.90	1.50	2.40	60	G	+/-10%	+/-10%	1.50-1.90	0.20	1.60
277	0.85	0.60	0.80	138	G				0.50	0.80
347	0.65	0.50	0.60	173	G				0.40	0.60

REGULATORY COMPLIANCE

- Complies with ANSI Standards
- **CSA Certified**
- cRUus Listed
- **UL Class H Thermal Insulation**






ULTRASAVE LIGHTING LTD.




Physical Characteristics


WIRING DIAGRAM




DIMENSIONS



А	2.50"
В	3.70"
Lead	12"
Weight	7 lbs



CAPACITOR



Temp. Rating	100°C
Capacitance	10.5uF+/-3%
Volts (min)	400 VAC
Туре	Oil Filled
Height	2.75"
Diameter	1.75"

ORDERING INFORMATION

Model #	Вох	Box Weight	Box Measurement LxWxH	Bulk	Bulk Weight	Bulk Measurement LxWxH
HD175-M57-A	1	6 lbs	7.50"x4.85"x3.25"	282	1,741.65 lbs	39.75"x41.50"x19.00"

ULTRASAVE LIGHTING LTD.

12-140 Amber Street, Markham, ON L3R 3J8 Tel 905.940.0888 Fax 905.940.0338

WWW.ULTRASAVE.CA