

FILM & OVERHEAD PROJECTION LAMPS

- Medium Prefocus Base - P28s
- 2 3/16" (55.5mm) & 3 1/2" (88.9mm) Light Center Length
- Medium Screw Base - E26
- 3" (76mm) Light Center Length

Watts	Ushio Ordering Code	Ushio Lamp Description	Volts	Dimensions mm			Filament Type	Approx Lumens lm	Color Temp K	Avg Life h	Burn Position	Fig No
				Dia (A)	MOL (B)	LCL (C)						
Medium Prefocus Base – P28S - 2 3/16" (55.5mm) LCL												
500	1000160	CZX/DAB	120	32.0	146	55.6	C-13D	12500	3200	25	BD	1
500	1000179	DEB	120	38.0	144	88.9	C-13D	9000	2850	800	BU	2
500	1000205	DMX	120	64.0	144	55.5	C-13	13200	3200	50	BD	3
500	1000211	DNW	120	64.0	145	55.5	C-13	10000	3050	500	BD/Hor	3
750	1000170	DDB/DDW	120	38.0	146	55.6	C-13D	20000	3250	25	BD	1
750	1000212	DPJ*	120	64.0	144	55.5	C-13D	19500	3200	25	BD	3
1000	1000217	DRB/DRC	120	64.0	144	55.5	C-13	28000	3250	50	BD	3
1000	1000218	DRS	120	64.0	144	55.5	C-13D	27400	3250	25	BD	3
1000	1000227	DWK	230	64.0	146	55.6	C-13	25000	3100	50	BD	3
Medium Screw Base – E26 - 3" (76mm) LCL												
500	1000204	DMS	120	64.0	144	76.2	C-13	13200	3200	50	BD	4
750	1000169	DCX	120	38.0	139.7	76.2	C-13D	19500	3200	25	BD	5

* Special Order Item




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5