## USHIO

### **HALOGEN PAR36 LAMPS**

PAR 36 SERIES



#### HALOGEN 12V PAR 36 LAMPS FOR **GENERAL LIGHTING**

USHIO's Halogen 12V PAR 36 lamps are built to withstand the demanding conditions of landscape use while still providing optimum performance in track lighting and retail applications. With a life rating of 4,000 hours and a flame-sealed lens, these lamps are designed to last twice as long as incandescent lamps and are protected against the adverse affects of moisture.

Not only do these Halogen lamps provide a longer life than incandescent lamps, they also offer up to 40% more energy savings compared to incandescents, improved lamp to lamp color consistency, and a brighter, whiter light source.

Available in 20W, 35W, & 50W lamps; Three premium beam patterns: Narrow Spot, Narrow Flood and Flood.

#### **FEATURES & BENEFITS**

- Flame sealed lens Ensures lamps will not be impacted by moisture
- 4,000 Hour lamp life Reduces maintenance costs
- Excellent color characteristics— Crisp, white Halogen light
- Energy savings Saves up to 40% in energy costs compared to higher wattage incandescent reflector lamps.

#### **APPLICATIONS**

- Commercial Landscape Lighting
- Architectural Lighting
- **Retail Lighting**
- Track Lighting
- Restaurants

**USHIO** PAR 36 Screw Terminals Universal Burn Posi-

tion

# 4.43 in

**CHARACTERISTICS & SPECIFICATIONS** 

Watts (W)	Ushio Ordering Code	Ushio Lamp Description	Volts (V)	Beam Angle	Beam Spread	Luminous Intensity (cd)	Avg Life (h)
20	1003539	20PAR36/NSP8/12V	12	8°	Narrow Spot	3500	4000
20	1003532	20PAR36/NFL20/12V	12	20°	Narrow Flood	1300	4000
20	1003531	20PAR36/FL30/12V	12	30°	Flood	750	4000
35	1003535	35PAR36/NSP8/12V	12	8°	Narrow Spot	7500	4000
35	1003534	35PAR36/NFL20/12V	12	20°	Narrow Flood	2500	4000
35	1003533	35PAR36/FL30/12V	12	30°	Flood	1400	4000
50	1003538	50PAR36/NSP8/12V	12	8º	Narrow Spot	13500	4000
50	1003537	50PAR36/NFL20/12V	12	20°	Narrow Flood	5000	4000
50	1003536	50PAR36/FL30/12V	12	30°	Flood	2000	4000

\*These lamps are low voltage lamps and require a transformer to operate.



Scan with a smartphone to view this product online.

Form No. S-PAR36/R-0213: The specifications on this sheet supercede all previously published specifications and may be subject to change for design and specification improvement without prior notice.

Diaduila uda al la u	
Distributed by:	
000 00 0	© 2013 USHIO America, Inc. All rights reserved.