



Core & Coil (71A) HPS > 400W

CORE & COIL HID HPS BAL 750W S111 277/347/480V C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

• General Characteristics

Lamp Type	750W HPS
Number of Lamps	1 piece
Line Voltage	277/347/480 V
Input Current (Operating)	3.1/2.5/1.78 A
Line Frequency	60 Hz
Circuit Type	CWA
Ballast Type	Magnetic HID
Base Model	71A86F5
Core Size	4 1/4 x 6
Suitable for Outdoor use?	Yes
Ignitor Catalog Number	LI561-H5
Ignitor Temp Rating	105°C
Capacitor value [µF]	75 MFD
Capacitor Catalog Number	7C750S28RA
Capacitor Requirements	280V
Capacitor Temp Rating	105°C
Capacitor Dia/Oval Dim	2.05 in
Capacitor Height	5 in
Family Name	Core & Coil HPS

• Operating Characteristics

Automatic restart	No
Input Voltage at Lamp Dropout	208/260/360 V
Nominal Open Circuit Voltage	225 V
Inp. Current (Open Circuit)	1.5/1.2/0.9 A

Input Current (Starting)	3/2.3/1.65 A
Input Current Short Circuit	2-3/1.6-2.4/1.1-1.7 A
Secondary ShortCircuit Current	9.5-11.7 A
Input Power Gear	840 W
Constant wattage deviation	Within Trapezoid
Ballast factor	1 -
Power Factor	0.90

• Wiring Characteristics

Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Allowed Wiring Config(Remote)	Yes
Max Dist. Ball to Lamp(Remote)	5'
Recommended Fuse	10/10/5 A

• System Chars on driver level

Rated Lamp Watts	750W
------------------	------

• Product Dimensions

Length A1	6 in
Length A2	5.4 in
Length A3	4.4 in
Width B1	4.3 in
Coil Depth C1	5.13 in
Stack Height C2	3.12 in
Width B2	3.9 in

PHILIPS

Core & Coil (71A) HPS > 400W

• Approval & Application Chars


Approbation Marks	ULR, CSA, RoHS
CE marking	No
VDE certificate	No
UL Listed	No
CSA certificate	Yes
CCC certificate	No
Chia Quality Certifi- cate	No
Temperature marking	E/D/D
CEC Listing	No
cUL certificate	No
EISA	No
ETL Certificate	No
FIDE Certificate	No
NOM certificate	No
RoHS Compliant	Yes
SASO Certificate	No
UL Recognized	Yes
ANSI Code	S111

HiPot Test (1 minute)	2000 V
HiPot Test (2 seconds)	2500 V
Open Circ Voltage Test (Volts)	200-245 V
UL Insulation Class	H(180°C)
UL Temperature Code	1029E

• Product Data


Product number	71A86F5500D
Full product name	HPS BAL 750W S111 277/347/480V C&C
Short product name	HPS BAL 750W S111 277/347/480V C&C
Pieces per Sku	1
Skus/Case	2
Bar code on pack	781087866559
Bar code on case	50781087866554
Logistics code(s)	913700540009
eop_net_weight_pp	10.719 kg

Dimensional drawing



CORE & COIL HID HPS BAL 750W S111 277/347/480V C&C

Product	A1 (Norm)	A2 (Norm)	A3 (Norm)	B1 (Norm)	B2 (Norm)	C1 (Norm)	C2 (Norm)
HPS BAL 750W S111 277/347/480V C&C	6	5,4	4,4	4,3	3,9	5,13	3,12





© 2014 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2014, March 20
data subject to change