

e-Vision Low Wattage 20-150W

E-VISION ELE MH BAL 70W M139/M143 120-277 50/60HZ

Low frequency electronic HID ballasts such as the Philips Advance e-Vision line constantly measure and adjust the wattage, optimizing delivery of the ceramic lamps' superior color properties. This makes ceramic metal halide operated by e-Vision ballasts the premier choice for many applications previously illuminated by either tungsten halogen or incandescent sources, such as retail lighting.

Product data

• General Characteristics

Lamp Type 70W MH Number of Lamps 1 piece Input Voltage 120-277 V 50/60 Hz Line Frequency Electronic HID Ballast Type Base Model IMH70DBLS Housing Housing Dimensions $4.3" \times 3.0" \times 1.5"$ Housing Material Metal Suitable for Outdoor use? Lifetime 90% 50000 hr surv.@Tcaselife

eVision

• Operating Characteristics

Family Name

Ignition time 1200 s
Input Power Gear 79-76 W
Ballast factor 1 Power Factor 0.90
Lamp Current Crest 1.8 Factor
Sound Rating A
Max THD 15 %

• Wiring Characteristics

Color input terminals
Color output terminals
No terminals

All leads = 11" Wire Length by Color Wire Type Stranded Allowed Wiring Yes Config(Remote) Allowed Wiring No Config(Tandem) Allowed Wiring No Config(Through) Max Dist. Ball to 3 Lamp(Remote)

• System Chars on driver level

Rated Lamp Watts 70

• Temperature Characteristics

T-case maximum 85 C

• Product Dimensions

 Length A1
 5.0 in

 Length A2
 4.3 in

 Length A3
 4.6 in

 Width B1
 3.0 in

 Height C1
 1.5 in

 Length A4
 2.0 in

 Width B2
 0.7 in

• Approval & Application Chars

EMC Immunity FCC Non-Consumer
CE marking No
ENEC certificate No
VDE certificate No
UI Listed Yes



e-Vision Low Wattage 20-150W

CSA certificate CEC Listing Yes No CSA Recognized No cUL certificate No **EISA** Νo FIDE Certificate Νo NOM certificate RoHS Compliant No Yes SASO Certificate Νo **UL** Recognized No

ANSI Code C98/M98, C139/M139, M143

• Product Data

Product number IMH70DBLSM

Full product name ELE MH BAL 70W M139/M143

120-277 50/60HZ


Short product name ELE MH BAL 70W M139/M143

120-277 50/60HZ

Pieces per Sku 1 Skus/Case 10


Bar code on pack 781087041215
Bar code on case 50781087041227
Logistics code(s) 913710258402
eop_net_weight_pp 0.686 kg

Dimensional drawing



E-VISION ELE MH BAL 70W M139/M143 120-277 50/60HZ

Product	A1 (Norm)	A2 (Norm)	A3 (Norm)	A4 (Norm)	A5 (Norm)	B1 (Norm)	B2 (Norm)	C1 (Norm)
ELE MH BAL 70W M139/M143 120-277 50/60HZ	5.0	4.3	4.6	2.0	-	3.0	0.7	1.5





© 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.