

DESCRIPTION

The Silhouette Wraparound LED is ideal for surface and chain hung general illumination luminaire for light commercial and residential applications. The high efficiency LED light engine from Ultrasave provides exceptional performance coupled with quality visual light.

SPECIFICATION FEATURES

Construction

Die formed 22 gauge galvanized steel painted high gloss white finish

Finish

22 gauge galvanized steel and high gloss enamel paint finish ensures maximum bonding and rust inhibition

Controls

The LED Silhouette is powered by Ultrasave Drivers

Shielding

Frosted LED lens offers visual comfort

Electrical

Long life LED system complete with electrical driver to deliver the optimal performance. LED's available in 4000K with a typical CRI: 80. Rated for 94,000 hours. Electronic Drivers are available in 120/277 and 347 Volt applications

Compliance

Modules and Drivers are UL recognized components and indoor luminaires are cULus listed

Warranty

5 years

Driver and Module Access

Drivers can be accessed by removing the lens and then the driver cover

SPW4-54LED04

Dimension

mm | 1155(L) x 210(W) x 70(D)
inch | 45.5"(L) x 8.3"(W) x 2.8"(D)




**SILHOUETTE
LED WRAPAROUND**

powered by
ULTRASAVE



ORDERING CODE, ENERGY AND PERFORMANCE DATA

	Model No.	Delivered Lumens (lm)	Input Watts (W)	Voltage (V)	Colour Temp. (K)	Efficacy (lm/W)	Status
	SPW4-54LED04	5900	63	120M / 347	4000K	94	Stock

OPTIONAL ACCESSORIES

Dimming Drivers (D) 120M/347V

SHIPPING DATA

Model No.
SPW4-54LED04**Weight**
3.3kg / 7.3lbs