

lighting Solutions closer to nature

DESCRIPTION

The EEL LED Small Wall Pack is an economical security accent and perimeter lighting for entranceways, garages and alleys. Optional factory-Installed photocell available.

SPECIFICATION FEATURES

Construction

Polycarbonate housing and lens secured to a die-cast aluminum base by two screws. The fixture is sealed with a silicone gasket for a water tight seal

Controls

The EEL LED Small Wall Pack is powered by Ultrasave Drivers and Modules for maximum performance and maximum energy savings

Electrical

Long-life LED system coupled with electrical driver to deliver optimal performance. LED's available in 4000K standard and optional 3500K and 5000K with CRI: 80. Rated for 94,000 hours. Electrical drivers are available for 120/277V applications

Driver and Module Access

Driver and modules can be removed by removing two screws that hold the lens and housing to the die-cast base

Finish

Durable polycarbonate bronze housing and prismatic lens with a bronze powder painted die-cast aluminum base

Reflectors

Modules are attached to high reflectance aluminum plate for more lumens uniformity

Shielding

Combination housing and prismatic diffuser provides an effective distribution of light

Compliance

Modules and Drivers are cULus approved and LED modules comply with LM-79 and LM-80 standards

Warranty


5 years




SMALL WALL PACK











ORDERING CODE, ENERGY AND PERFORMANCE DATA

Model No.	Delivered Lumens (Im)	Input Watts (W)	Voltage (V)	Colour Temp. (K)	Efficacy (Im/W)	Status
WHLF2-11LED02	1100 1100	11.5 11.5	120M 120M	4000K 3500K / 5000K	95 90 / 100	Stock MTO

OPTIONAL ACCESSORIES
PC-SWP PHOTO CELL | Photo Cell for Small Wall Pack

SHIPPING DATA Model No. WHLF2-11LED02

Weight 1.25kg / 3lbs

