

Specification Sheet LED-9630 Grow Light 150 Watt Fixture

LED GROW LIGHTS BY LIGHT EFFICIENT DESIGN







Description:

150 watt Grow Light Fixture is UL listed for wet locations and meets the ingress protection requirements of IP65. This fixture can be used in a wide variety of applications and environments. Two versions of this fixture are available:

> LED-9630G operates on 120-277 VAC LED-9630G-HV operates on 200-480 VAC

Several of the benefits of this fixture include:

- Light Spectrum is efficiently absorbed by plants
- Save money on maintenance and electricity
- UL listed for wet location
- Long lasting 50,000 hour expected LED life
- · Cool running so light can be mounted close to plants


Applications:

This lamp can be used as a primary or supplemental light source for almost any type of indoor or greenhouse growing.

The light output has a very wide angle. It will provide the greatest benefit when mounted relatively close to the plants.

Notes:

- Installing surge/lightning protectors is highly recommended to eliminate premature failure caused by surges and other power fluctuations
- All specification information falls within a +/- 5% range and is subject to change without notice.
- Light Efficient Design is providing this information to the general public. Please
 note that all products contained herein are trademarked, copyrighted and/or
 have patents pending. Any use of these designs is strictly prohibited without
 prior written consent. Light Efficient Design protects its proprietary information
 vigorously in the courts of the United States of America.



Technical Specifications	
Туре	Fixture
Mounting	Bracket
Shell Material	Aluminum / Glass
Input Voltage	120-277 VAC /
9630G/9630-HV	200-480 VAC
Power	
Consumption	150 watts
Power Factor	>95
PAR Output	
(Center)	
12 inches	653 μmol/m²/s
24 inches	210 µmol/m²/s
36 inches	104 µmol/m²/s
LED Colors	Red, White, Blue
Coverage area	up to 4' by 4'
Dimmable	No
Beam Angle	120°
Rated LED Life	50,000 hours
Dimensions	
Height	8.0 inches
Diameter	16.5 inches
Mercury/Lead	
content	None
Warranty	5 year limited