

GU10LED6W

6 Watt GU10 LED Lamp, GU10 Base
120V

Job Information		
Project Name	GU10LED6W-30K-WH	Type
Location	Canadalite.com	
Quantity		Date
Contact/Phone	1(888)887-7038	
Notes		

Features

Lighting Performance

Constructed with an aluminum heat sink and high powered Nichia® LED, this lamp has a 6 watt power consumption that produces up to 390 lumens. The LED lamp is driven by 120V AC input power from GU10 socket.

Colour Temperature

Available in 3000K and 4000K correlated colour temperatures. It maintains a colour rendering index of 80+.

Lumen Maintenance

The LED lamp reduces ongoing maintenance costs with a 40,000 hours rated LED life, while maintaining 70% of initial lumen output after 50,000 hours projected life.

Thermal Management System

Durable passive aluminum heat sink is used to manage heat generated by the LED lamp. The heat sink employs an

internal fin design that wraps around the lamp and lowers air friction, which provides for a natural convection of heat into the surrounding environment, while maintaining a smooth outer surface similar with a regular halogen lamp.

Dimming

The LED lamp supports dimmable functionality (see list of compatible dimmers on page 2).

Beam Spread

With a high efficiency, precision engineered lens, the LED lamp is capable of providing 38 degree beam spread.

Operating Temperature

-40°C~40°C (-40°F~104°F)

Environment

Suitable for damp locations. Not suitable for totally enclosed luminaires.

SPECIFICATION	
Approved Location	Damp
Base	GU10
Beam Angle	38°
CCT	3000K
Certification	cULus
CRI	80+
Dimming	Yes
Dimming Tech.	TRIAC
Energy Star®	Yes
Lamp Type	GU10
LM79	Yes
LM80	Yes
Lumens	380
Lumens per watt	63.3
Max. Operating Temp.	40°C
Min. Start Temp.	-40°C
Projected Lumen Maintenance	70% @ 50,000 hrs
Rated Life	40,000 HRS
Primary Voltage	120V
Warranty	5 Years
Wattage	6




Description

This 6 watt line voltage LED lamp is UV and IR radiation free, minimizing discoloration and fading of materials. LED technology reduces energy and maintenance costs when compared to conventional light sources. Suitable for both residential and commercial applications, approved for damp locations. Can be used as a replacement to line voltage halogen lamps.



*Available in 3000K

Notes: For additional options please consult your Liteline representative. Due to our continued efforts to improve our products, product specifications are subject to change without notice.



Ordering Guide



GU10LED6W-30K-WH*

6W Line voltage LED MR16 GU10 lamp, 120V, 3000K, 380 lumens, White.



GU10LED6W-40K-WH

6W Line voltage LED MR16 GU10 lamp, 120V, 4000K, 390 lumens, White.



Compatible Dimmers

Brand	Model	Load	Maximum Number of Lamps per Dimmer
Leviton	6613-P	600W	6
	6633-P	600W	6
	6681	600W	6
	6683	600W	6
	IPI06	600W	6
Kaoyi	KHD-154U	600W	6
Legrand	CD703-PW	700W	7
	CDLV703-PW	700W	7
	D703-PTC	700W	7
	DRD4-W	600W	6
	DLV703-PLA	700W	7
Lutron	AY-600P	600W	6
	CN-600P	600W	6
	D-603PH	600W	6
	DV-600PH	600W	6
	DV-603PG	600W	6
	DVELV-300P	300W	3
	GL-600H	600W	6
	LGCL-153PLH	600W	6
	NELV-450	450W	4
	S-600	600W	6
	SELV-300P	300W	3
	TG-600PNLH	600W	6
	TGCL-153PH	600W	6
	TT-300NLH	300W	3