

P20LED8W

8 Watt PAR20 LED Lamp, E26 Base 120V

| | Job Information | | | |
|--|-----------------|-------------------|------|--|
| | Project Name | P20LED8W-30KFL-WH | Туре | |
| | Location | Canadalite.com | | |
| | Quantity | | Date | |
| | Contact/Phone | 1(888)887-7038 | | |
| | Notes | | | |

Features

Lighting Performance

Constructed with an aluminum heat sink and high powered Citizen® LED, this lamp has a 8 watt power consumption that produces up to 500 lumens. The LED lamp is driven by 120V AC input power from medium base socket.

Colour Temperature

Available in 3000K and 4000K correlated colour temperatures. It maintains a colour rendering index of

Lumen Maintenance

The LED lamp reduces ongoing maintenance costs with a 40,000 hours rated LED life, while maintaining 70% of initial lumen output after 50,000 hours projected life.

Thermal Management System

Durable passive aluminum heat sink is used to manage heat generated by the LED lamp. The heat sink employs an

internal fin design that wraps around the lamp and lowers air friction, which provides for a natural convection of heat into the surrounding environment, while maintaining a smooth outer surface similar with a regular halogen lamp.

Dimming

The LED lamp supports dimmable functionality (see list of compatible dimmers on page 2).

Beam Spread

With a high efficiency, precision engineered lens, the LED lamp is capable of providing 40 degree beam spread; and also 25 degree beam

Operating Temperature -40°C~40°C (-40°F~104°F)

2-1/2"

63mm

Environment

Suitable for damp locations. Not suitable for totally enclosed luminaires.

3-3/8"

86mm

| SPECIFICATION | | | | |
|----------------------|---------------------|--|--|--|
| Approved Location | Damp | | | |
| Base | E26 | | | |
| Beam Angle | 40° / 25° | | | |
| CBCP | 827 / 1577 | | | |
| CCT | 3000K | | | |
| Certification | cULus | | | |
| CRI | 80+ | | | |
| Dimming | Yes | | | |
| Dimming Tech. | TRIAC | | | |
| Energy Star® | Yes | | | |
| Lamp Type | PAR20 | | | |
| LM79 | Yes | | | |
| LM80 | Yes | | | |
| Lumens | 490 / 470 | | | |
| Lumens per watt | 61.3 / 58.8 | | | |
| Max. Operating Temp. | 40°C | | | |
| Min. Start Temp. | -40°C | | | |
| Projected Lumen | 70% @ 50,000 hrs | | | |
| Maintenance | 70 /0 @ 30,000 1113 | | | |
| Rated Life | 40,000 HRS | | | |
| Voltage | 120V | | | |
| Warranty | 5 Years | | | |
| Wattage | 8 | | | |



Description

This 8 watt line voltage LED lamp is UV and IR radiation free, minimizing discoloration and fading of materials. LED technology reduces energy and maintenance costs when compared to conventional light sources. Suitable for both residential and commercial applications, approved for damp locations. Can be used as a replacement to line voltage halogen lamps.





in 3000K

Notes: For additional options please consult your Liteline representative. Due to our continued efforts to improve our

products, product specifications are subject to change without notice.

Ordering Guide



P20LED8W-30KFL-WH*

8W Line voltage LED PAR20 E26 flood lamp, 120V, 3000K, 490 lumens, White.



P20LED8W-40KFL-WH

8W Line voltage LED PAR20 E26 flood lamp, 120V, 4000K, 500 lumens, White.



P20LED8W-30KSP-WH*

8W Line voltage LED PAR20 E26 spot lamp, 120V, 3000K, 470 lumens, White.







Compatible Dimmers

| Brand | Model | Load | Maximum Number of Lamps per Dimmer |
|----------|-------------|------|---------------------------------------|
| | 6613-P | 600W | 8 |
| | 6633-P | 600W | 8 |
| Leviton | 6681 | 600W | 8 |
| Levitori | 6683 | 600W | 8 |
| | 6684 | 600W | 8 |
| | IPI06 | 600W | 8 |
| Kaoyi | KHD-154U | 600W | 8 |
| - | CDLV703-PW | 700W | 9 |
| Lagrand | D703-PTC | 700W | 9 |
| Legrand | DRD4-W | 600W | 8 |
| | DLV703-PLA | 700W | 9 |
| | AY-600P | 600W | 8 |
| | CN-600P | 600W | 8 |
| | D-603PH | 600W | 8 |
| | DV-600PH | 600W | 8 |
| | DV-603PG | 600W | 8 |
| | DVCL-153PL | 600W | 8 |
| | DVELV-300P | 300W | 4 |
| Lutron | GL-600H | 600W | 8 |
| | LGCL-153PLH | 600W | 8 |
| | NELV-450 | 450W | 6 |
| | S-600 | 600W | 8 |
| | SELV-300P | 300W | 4 |
| | TG-600PNLH | 600W | 8 |
| | TGCL-153PH | 600W | 8 |
| | TT-300NLH | 300W | 4 |