



Single Colour Indoor LED Strip Light, 24V Cabinet, Cove & Display

Job Information		
Project Name		Туре
Location		
Quantity		Date
Contact/Phone		
Notes		

#### **Features**

## **Operation Performance**

Energy efficient, at 4W per strip, provides expandability up to 16 sections per 60W 24V driver or hardwire box (sold separately). These LED strips are designed for indoor use only (dry location), and are operated at an ambient operating temperature between -20°C and +50°C.

#### Lighting Performance

Thermally efficient for illuminating sensitive perishables and UV sensitive apparel, artwork and collectibles; these LEDs are cool to the touch and provides 120° linear beam spread.

#### **Colour Temperature**

Available in three colour temperatures:

- Warm White (3000K ±200K)
- Neutral White (4100K ±200K)
- Cool White (6500K ±500K)

#### Lumen Maintenance

The LEDs reduces ongoing maintenance with an 25,000 hours rated LED life, at 70% average lumens.

- Warm White 250 lumens per foot.
- Neutral White 270 lumens per foot.
- Cool White 280 lumens per foot.

#### Linkable

A built-in jointer for continuous uninterrupted lighting offers a noshadow linking capability up to 16 strips. LED strips may be connected further apart using flexible 6" (LED-STR-6-BC – sold separately) or 12" (LED-STR-12-BC - sold separately) linking cable. A power feed (LED-STR-PF - sold separately) is required to connect to plug-in driver or hardwire box.

### Dimmable

These LED strips offer dimmable

12" 305mm functionality when used with a dimming driver (sold separately).

#### Mounting

Available with both 0° and 35° mounting clips with screws provided for surface mounting applications.

## Certification

cULus listed.



## Description

LED-STR-12 is a single 12" (305mm) undercabinet LED strip light. It provides ample illumination for effective residential, retail and light commercial displays. The LED-STR-12 is ideal for kitchen counters, curious and cabinets. It can be expanded for continuous uninterrupted lighting



Notes: Accessories should be ordered separately. For additional options please consult your Liteline representative. Due to our continued efforts to improve our products, product specifications are subject to change without notice.



#### **Ordering Guide**

LED-STR-12WW

12" (305mm) LED strip light, warm white.

LED-STR-12NW 12" (305mm) LED strip light, neutral white.

LED-STR-12CW 12" (305mm) LED strip light, cool white.

## Accessories

# LED-STR-PF

12" single colour power feed for LED strip light.









Wire splice extension kit, 24V.

I FD-SP-4 Optional harness for up to 4 runs, 24V



13/16"

21mm

LED-DVR-24V-60W 60W Indoor LED plug-in driver, 24V.



LED-HWB-24V-60W 60W Indoor LED hardwire box, 24V.



LED-HWBDIM2-24V-40 LED 2-wire dimmable driver, 24V, 40W.





I FD-DIM 24V LED touch dimmer, 24V.



LITELINE CORPORATION info@liteline.com www.liteline.com

8 Abacus Road Brampton, Ontario Canada L6T 5B7

PHONE | TÉLÉPHONE 416-996-1856 1-866-730-7704

FAX | TÉLÉCOPIEUR 905-794-1990 1-888-738-9736

REV5/6.25.13