

VENUS Line Voltage Track Fixture

Track Systems

| Job Information | | |
|-----------------|----------------|------|
| Project Name | | Туре |
| Location | Canadalite.com | |
| Quantity | | Date |
| Contact/Phone | 1(888)887-7038 | |
| Notes | | |
| | | |

Features

Body

Constructed of die cast aluminum which provides superior strength and rigidity. Softened edges adds up to the low profile aesthetic design.

Lamping

Porcelain socket for 120V MR16 GU10 lamps, 50 watts max. A high temperature glass shield is included, mounted to front of lamp fixture.

Adjustability

Lamp housing is controlled with an adjustable yoke that would provide custom aiming; 330° horizontal rotation and 90° vertical rotation.

Dimming

The track fixture is dimmable when used with electronic line voltage rated dimming controls only. 120V / 60Hz input; 120V output; 50W maximum load.

Compatibility

Liteline track fixtures are compatible with Juno®, Halo®, Lightolier® and most brands configured to Halo® track system


Labels

• cULus listed.



Description

The VENUS is a die cast construction fixture with clear acrylic disk and no visible socket wire. The handle at the back of the fixture makes it easy to reposition the fixture to any desired angle.



Connector Compatibility Chart



Style



Style



Style



Style

Liteline® Lightolier® Halo®



Notes: Accessories should be ordered separately. For additional options please consult your Liteline representative. Juno is a registered trademark of Juno Lighting Group. Halo is a registered trademark of Cooper Lighting. Lightolier is a registered trademark

Due to our continued efforts to improve our products, product specifications are subject to change without notice.

Ordering Guide



VS1040-BK-120V-MR

VENUS black track fixture, 120V.



VS1040-WH-120V-MR

VENUS white track fixture, 120V.