#### **SPECIFICATION**













### LED EDGE-LIT EXIT SIGN

**NX-EMRMEPB** 

#### **Specification**

PRODUCT NAME: LED EDGE-LIT EXIT SIGN

MODEL NO.: **NX-EMRMEPB** 

SPECIFICATION: AC120-347V; 50/60Hz; 1W

**WORKING TEMP:** 5-30(°C) 0.95 **POWER FACTOR:** 

>85 CRI(RA):

**Black Color** COLOR:

LIGHT SOURCE: SMD 80 Lm LUMEN:

50000 hrs LIFE TIME:

BATTERY: Ni-Cd Battery 3.6V 800MAH

SELF-POWERED: 120 mins

11.06\*1.61\*9.53 inch PRODUCT SIZE:

IP20 IP:

**APPLICATION:** Shop, Hotel

5 years fixture, 3 years battery **WARRANTY:** 

STANDARD: CSA COLOR TEMP: 6500K






### Feature:

- \*Super Bright LED Light Source
- \*127-347V universal voltage
- \*Two wire design for easy installation
- \*Ni-Cad Battery 3.6V 800mAH
- \*CSA approved 120 mins battery backup time
- \*Universal Mounting: Ceiling mounting, Wall mounting and End mounting;
- \*Single/Double side installation
- \*Suitable for damp locations
- \*Comes with 3pcs pictograms (without arrow, with left arrow and with right arrow)

## **Product Dimension**



# Applications:

Suitable for commercial and institutional place: Apartment, hotel, shop, office, school, hospital ...etc.







## Warning:

- Review the diagrams thoroughly before beginning.
- All electrical connections must be in accordance with local codes, ordinances and the National Electric Code.
- Disconnect power at fuse or circuit breaker before installing or servicing.
- Do not use outdoors.
- Do not mount in hazardous locations or near gas or electric heaters.
- Do not let power cords touch hot surfaces.
- Equipment should be mounted in locations and at heights where it will not be subject to tampering by unauthorized personnel.
- The use of accessory equipment is not recommended by the manufacturer.
- Do not use this equipment other than intended use.
- All servicing should be performed by qualified personnel only.
- Allow battery to charge for 24hrs before first use.





