SPECIFICATION









LED EXIT SIGN

NX-EMRMS

Specification

PRODUCT NAME: LED EXIT SIGN

MODEL NO.: **NX-EMRMS**

SPECIFICATION: AC120-347V; 50/60Hz; 1W

WORKING TEMP: 5-30(°C)

0.95 **POWER FACTOR:**

>85 CRI(RA):

White Color COLOR:

LIGHT SOURCE: SMD

90 Lm LUMEN:

50000 hrs LIFE TIME:

Ni-Cd battery 3.6V 1000mAH BATTERY:

120 mins SELF-POWERED:

12.36*2.13*7.48 inch PRODUCT SIZE:


IP20 IP:

APPLICATION: Shop, Hotel

5 years fixture, 3 years battery **WARRANTY:**

CSA STANDARD:

COLOR TEMP: 6500K








Feature:

- *Super Bright LED Light Source
- *127-347V universal voltge
- *Two wire design for easy installation
- *Ni-Cad Battery 3.6V 1000mAH
- *CSA approved 120 mins battery backup time
- *Universal Mounting: Ceiling Mounting, Wall mouting and End mounting;
- *Single/Double side installation
- *Suitable for damp locations
- *Comes with 3pcs pictograms(without arrow, with left arrow and with right arrow)

Product Dimension



Applications:

Suitable for commercial and institutional place: Apartment, hotel, shop, office, school, hospital ...etc.







Warning:

- 1. READ AND FOLLOW ALL SAFETY INSTRUCTIONS.
- 2. For Indoor use ONLY.
- 3. Do not let power cords touch hot surfaces.
- 4. Do not install near gas or electric heaters.
- 5. Use caution when servicing batteries. Battery acid can cause burns to skin and eyes. If acid is spilled on skin or eyes, flush acid with fresh water and contact a physician immediately.
- 6. Equipment should be mounted in locations and at heights where unauthorized personnel will not readily subject it to tampering.
- 7. The use of accessory equipment not recommended by manufacturer, may cause an unsafe condition, and will void the unit's warranty. .
- 8. Do not use this equipment for other than its intended purpose.
- 9. Servicing of this equipment should be performed by qualified service personnel.
- 10. SAVE THESE INSTRUCTIONS FOR FUTURE REFERENCE.



