

Date:	Project Name:
Type:	Part Number:



# PL LAMPS

## FEATURES

- Replacement for Conventional 9W, 13W, 18W, 26W, and 42W PL Lamps
- Directly Compatible with Most Existing CFL Ballasts(4-Pin & 2-Pin)
- Line Voltage(120-277V)/Bypass ballast( 2-Pin Only)
- Suitable for use in enclosed fixture
- Suitable for use in dry and damp locations
- Rated Lifetime L70(hrs): >50,000
- Operating temperature: -4°F to +113°F (-20°C to +45°C)
- 4 Pin MCCT Switch
- 5 year warranty

## APPLICATIONS

- General Lighting
- Recessed Down Lights
- Display Cases
- Damp Location Installation



Date:	Project Name:
Type:	Part Number:

## SPECIFICATION

ORDER#	MODEL#	WATTS	VOLTAGE (V)	LUMENS	BASE TYPE	BEAM ANGLE	CCT (K)	DLC
R24009	WLL-LED6/2P/MCCT	6W	120-277V/BF	550 lm	GX23	120°	27/30/35/40/50K	No
R24007	WLL-LED9/4P/H/MCCT	9W	BF	1100 lm	G24Q	120°	30/35/40K	Yes
R24008	WLL-LED9/4P/V/MCCT	9W	BF	1100 lm	G24Q	120°	30/35/40K	Yes

## DIMENSIONS

30.5mm (1.2")



162.6mm  
(6.4")

**GX23**

40.6mm (1.6")



162.6mm  
(6.4")

**G24Q**

71.1mm (2.8")



134.6mm  
(5.3")

**G24Q**