# Technical Data Sheet Jupiter®-2



## Description

These high efficiency large wallpak fixtures can be used for outdoor wall mount applications, including parking areas, loading docks, security lighting, waterfronts, recreational areas, and perimeter lighting. The functional design includes models that range from 250W - 400W metal halide or 250W - 400W high pressure sodium.

#### Construction

The housing is formed of die-cast aluminum and includes ½" conduit entries on the top (2), sides (2), and back (2). The side hinged door includes a rubber gasket.



#### Finish

The housing is finished in a durable polyester coat, in bronze or white colours.

#### Diffuser

The fixture features a specular pure anodized aluminum reflector inside a prismatic glass lens.

#### Electrical

All models are CSA approved for outdoor use, and are wired with UL listed or CSA approved CWA high power factor ballasts for voltages ranging from 120V - 600V, 60 Hz operation.

### Options


Options include photocontrols and wire guards.


# Ordering Information

Model	Lamp Type	Voltage	Optional Photocontrol	Housing Colour
Jupiter - 2	250W - MH 400W - MH 250W - HPS 400W - HPS	120V 208V 240V 277V 347V 480V 600V	PC IB (internal button) PC ES (external swivel)	Bronze White









**www.canadalite.com** Tel:1(888)459-6938 Fax:1(888)908-9455

All specifications are subject to change without notice. Actual performance may vary depending on operating conditions.

Email: info@canadalite.com

