

| Date: | Туре: |
|---------------|--------------|
| Project Name: | Part Number: |

LED CANDLE LIGHT FILAMENT















APPLICATIONS

- Commercial Lighting
- Decorative Lighting
- Enclosed Recessed Fixture
- Damp Location Installation

FEATURES

- LED with a traditional incandescent design
- Smooth dimming with existing installations
- Uniform and consistent color
- 320° omni-directional light source
- 15,000 hours lifespan or 3-year warranty

SPECIFICATION

| ORDER # | MODEL# | BASE TYPE | LUMENS OUTPUT | BEAM ANGLE | EQUIVALENT WATTAGE | WATTS | INPUT VOLTAGE | POWER FACTOR | ССТ | CRI | DIA x MOL |
|---------|--------------------------|--------------|------------------|---------------|-----------------------|-------|------------------|-----------------|-------|-----|---------------|
| R21501 | RENO-Candle-E12-5W-2700K | E12 | 500lm/W | 320° | 60W | 5W | 120V AC | 0.9 | 2700K | 83 | 1.37"× 3.66" |
| R21503 | RENO-Amber-6W-2700K | E26 | 600lm/W | 320° | 60W | 6W | 120V AC | 0.9 | 2700K | 83 | 1.38"x 3.81" |
| R21502 | RENO-Amber-6W-2400K | E26 | 450lm/W | 320° | 40W | 6W | 120V AC | 0.7 | 2400K | 83 | 2.51" x 6.56" |



