



EXIT/EMERGENCY

FEATURES

- Easy to install
- Long battery life
- Environmentally friendly
- Energy saving
- Single and double-sided installation
- Wall and ceiling mountable

LISTINGS

- UL Listed for Dry/Damp locations
- Safety and performance in accordance with UL-924
- Title 20 and Title 24 (JA8) Compliant (90CRI models only)

PERFORMANCE

- ≥90 minutes of emergency operating power at the rated wattage

ELECTRICAL SPECIFICATIONS

- Input voltage: 120/277V
- Input power: 1W/3.5W/4W
- Power Factor: >0.5
- Emergency operation: ≥90 mins
- Recharge: 24 hrs

THERMAL

- 32°F to 104°F (0°C to 40°C) operating temperature

CONSTRUCTION

- Injection molded ABS and polycarbonate housings

WARRANTY

- 3 year limited warranty; see eiko.com for warranty details

project name	type
catalog number	
comments	voltage
approved by	date



EXIT-R



EXIT-G



EXIT/EM-R



EXIT/EM-G



EML

(Fixtures available in white or black housing)

APPLICATIONS

- Emergency and exit lighting



RoHS
Compliant



EML
only

ORDERING INFORMATION

EXAMPLE: EXIT/EM-R-BK

Model	Sign Color	Housing Color
EXIT - Exit Sign	R - Red	W - White
EML - Emergency Light	G - Green	BK - Black
EXIT/EM - Exit Sign with Emergency Light		

PERFORMANCE SUMMARY

Order Code	Item #	Description
11033	EXIT-R-W	Exit Sign Red White Housing
11034	EXIT-G-W	Exit Sign Green White Housing
11035	EXIT-R-BK	Exit Sign Red Black Housing
11036	EXIT-G-BK	Exit Sign Green Black Housing
11037	EXIT/EM-R-W	Exit Sign Red with Emergency Light White Housing
11038	EXIT/EM-G-W	Exit Sign Green with Emergency Light White Housing
11039	EXIT/EM-R-BK	Exit Sign Red with Emergency Light Black Housing
11040	EXIT/EM-G-BK	Exit Sign Green with Emergency Light Black Housing
11041	EML-W	Emergency Light White Housing
11042	EML-BK	Emergency Light Black Housing

DIMENSIONS

