



## PAR LAMPS : PAR 20, 30, 30S, 38

### DESCRIPTION

LED PAR Replacement Lamps directly replace incandescent PAR lamps at a fraction of the energy cost.

### FEATURES

- Compatible with a wide array of dimmers
- +25,000 hour rated life for ENERGY STAR® Approved lamps\*
- 50,000 hour design life\*\*
- Up to 80% electricity savings vs. halogen
- No mercury or UV/IR emissions
- Shatter-resistant for reduced risk of injury and breakage

### WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

### APPLICATIONS

- Recessed / Track Lighting
- Property Management
- Accent / Display Lighting
- Retail / Residential
- Hospitality
- Houses of Worship
- Healthcare
- Task Lighting



\* Early initial qualification for ENERGY STAR allows for directional lamp life claims of 25,000 hours (L70) with 3,000 hour actual test data, LM80 data and in-situ temperature measurements. As the lamps pass ENERGY STAR requirements, manufacturers may increase the lifetime of a product as dictated by ENERGY STAR guidelines. See [http://www.energystar.gov/index.cfm?fuseaction=products\\_for\\_partners.showLightbulbs](http://www.energystar.gov/index.cfm?fuseaction=products_for_partners.showLightbulbs) for further details.

\*\* Design life is based on engineering testing and probability analysis



<b>PERFORMANCE</b>	Power Consumption	7W	11W	13W	15W
	Lumens	500	850	1,050	1,250
	Efficacy (LPW)	71	77	81	83
	CRI	80+			
	Beam	30°, 40°			
	CCT	2700K, 3000K, 4000K, 5000K			
	Life (L70)	25,000 hours*			
<b>ELECTRICAL</b>	Power Factor	>0.7			
	THD	<20%			
	Input Voltage	120V			
<b>CONSTRUCTION</b>	Operating Temperature	-40°F to 104°F (-40°C to 40°C)			
	Base	E26			
<b>LISTINGS</b>	Certification(s)	ENERGY STAR® Rated; cULus Classified			
	Material Usage	RoHS Compliant; no mercury or lead			
	Environment	Wet or Damp location rated; not for use in enclosed fixtures, with electronic timers, photo-cells, or motion/occupancy sensors			

## PERFORMANCE SUMMARY

Order Code	Item #	Lumens	Watts	CCT	CRI	Beam	MOL	MOD	Life/Hours	Replaces Incan.	Damp Location Rated	Wet Location Rated	ES
10782	LED7WPAR20/FL/827-DIM-G9	500	7W	2700K	80+	40°	3.19"	2.48"	25,000	50W			★
10783	LED7WPAR20/FL/830-DIM-G9	500	7W	3000K	80+	40°	3.19"	2.48"	25,000	50W			★
10784	LED7WPAR20/FL/840-DIM-G9	500	7W	4000K	80+	40°	3.19"	2.48"	25,000	50W			★
10785	LED7WPAR20/NFL/827-DIM-G9	500	7W	2700K	80+	30°	3.19"	2.48"	25,000	50W			★
10786	LED7WPAR20/NFL/830-DIM-G9	500	7W	3000K	80+	30°	3.19"	2.48"	25,000	50W			★
10787	LED7WPAR20/NFL/840-DIM-G9	500	7W	4000K	80+	30°	3.19"	2.48"	25,000	50W			★
10766	LED11WPAR30/FL/827-DIM-G9	850	11W	2700K	80+	40°	4.53"	3.74"	25,000	75W			★
10767	LED11WPAR30/FL/830-DIM-G9	850	11W	3000K	80+	40°	4.53"	3.74"	25,000	75W			★
10768	LED11WPAR30/FL/840-DIM-G9	850	11W	4000K	80+	40°	4.53"	3.74"	25,000	75W			★
10769	LED11WPAR30/FL/850-DIM-G9	850	11W	5000K	80+	40°	4.53"	3.74"	25,000	75W			★
10770	LED11WPAR30/NFL/827-DIM-G9	850	11W	2700K	80+	30°	4.53"	3.74"	25,000	75W			★
10771	LED11WPAR30/NFL/830-DIM-G9	850	11W	3000K	80+	30°	4.53"	3.74"	25,000	75W			★
10772	LED11WPAR30/NFL/840-DIM-G9	850	11W	4000K	80+	30°	4.53"	3.74"	25,000	75W			★
10773	LED11WPAR30S/FL/827-DIM-G9	850	11W	2700K	80+	40°	3.62"	3.74"	25,000	75W			★
10774	LED11WPAR30S/FL/830-DIM-G9	850	11W	3000K	80+	40°	3.62"	3.74"	25,000	75W			★
10775	LED11WPAR30S/FL/840-DIM-G9	850	11W	4000K	80+	40°	3.62"	3.74"	25,000	75W			★
10776	LED11WPAR30S/NFL/827-DIM-G9	850	11W	2700K	80+	30°	3.62"	3.74"	25,000	75W			★
10777	LED11WPAR30S/NFL/830-DIM-G9	850	11W	3000K	80+	30°	3.62"	3.74"	25,000	75W			★
10788	LED13WPAR38/FL/827-DIM-G9	1,050	13W	2700K	80+	40°	5.12"	4.72"	25,000	120W	💧		★
10789	LED13WPAR38/FL/830-DIM-G9	1,050	13W	3000K	80+	40°	5.12"	4.72"	25,000	120W	💧		★
10790	LED13WPAR38/FL/840-DIM-G9	1,050	13W	4000K	80+	40°	5.12"	4.72"	25,000	120W	💧		★
10778	LED15WPAR38/FL/827-DIM-G9	1,250	15W	2700K	80+	40°	5.12"	4.72"	25,000	150W	💧		★
10779	LED15WPAR38/FL/830-DIM-G9	1,250	15W	3000K	80+	40°	5.12"	4.72"	25,000	150W	💧		★
10780	LED15WPAR38/FL/840-DIM-G9	1,250	15W	4000K	80+	40°	5.12"	4.72"	25,000	150W	💧		★
10781	LED15WPAR38/FL/850-DIM-G9	1,250	15W	5000K	80+	40°	5.12"	4.72"	25,000	150W	💧		★
10069	LED15WPAR38/FL/827-DIM-G8	1,250	15W	2700K	80+	40°	5.16"	4.72"	25,000	120W		💧	★
09990	LED15WPAR38/FL/830-DIM-G8	1,250	15W	3000K	80+	40°	5.16"	4.72"	25,000	120W		💧	★
09991	LED15WPAR38/FL/840-DIM-G8	1,250	15W	4000K	80+	40°	5.16"	4.72"	25,000	120W		💧	★
09992	LED15WPAR38/FL/850-DIM-G8	1,250	15W	5000K	80+	40°	5.16"	4.72"	25,000	120W		💧	★

NOTE: Use order code when ordering. 💧Wet Location Rated ★ENERGY STAR® Approved

## DIMENSIONS

