



T8 TUBES : BYPASS : HIGH-LUMEN : SINGLE-ENDED

DESCRIPTION

LED T8 Replacement Lamps directly replace fluorescent T8 lamps at a fraction of the energy cost.

FEATURES

- Solid state replacement for 4 ft. T8 or T12 G13 base linear fluorescent
- Single-end powered, operates on 120V-277V line voltage
- Frosted lens for uniform diffuse appearance
- No external ballast or driver required
- Ultra-high performance LEDs deliver 135 lpw
- Up to 50% instant energy savings
- Existing fixture maintains original UL compliance
- Integral 120~277V drivers provide easy installation
- For use with non-shunted tombstone lampholders
- Non-dimmable

WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

APPLICATIONS

- Commercial
- Industrial
- Hospitality
- Education
- Healthcare
- Retail



PERFORMANCE	Power Consumption	26W
	Lumens	3,500
	Efficacy (LPW)	135
	CRI	80+
	CCT	4000K, 5000K
	Life (L70)	50,000 hours
ELECTRICAL	Power Factor	≥0.9
	THD	<20%
	Input Voltage	120-277V
CONSTRUCTION	Operating Temperature	-4°F to 113°F (-20°C to 45°C)
	Base	G13
	Lens	Frosted
LISTINGS	Certification(s)	DesignLights Consortium® Qualified; cULus Classified; FCC
	Material Usage	RoHS Compliant; no mercury or lead
	Environment	

PERFORMANCE SUMMARY

Order Code	Item #	Length	Lumens	Watts	LPW	CCT	CRI	Beam	Wiring	Life/Hours	DLC
10467	LED26WT8/48/840-G8D	4'	3,500	26W	135	4000K	80+	240°	Single-Ended	50,000	✓
10468	LED26WT8/48/850-G8D	4'	3,500	26W	135	5000K	80+	240°	Single-Ended	50,000	✓

NOTE: Use order code when ordering. ✓DesignLights Consortium Qualified

WIRING DIAGRAM

