



LED PLL : LINE VOLTAGE/BALLAST BYPASS

DESCRIPTION

LED PLL Lamps directly replace compact fluorescent PLL lamps and operate on line voltage, eliminating ballast compatibility concerns.

FEATURES

- Solid state direct replacement for 2' 40W PLL compact fluorescent lamps with 2G11 base
- Operates on 120-277V line voltage
- Frosted lens for uniform diffuse appearance
- Up to 50% instant energy savings
- Instant-On with no warm up like fluorescents
- Suitable for use in totally enclosed fixtures
- Frosted glass lens reduces visual glare

WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

APPLICATIONS

- Retail
- Hospitality
- Office
- Ceiling Luminaires



PERFORMANCE	Power Consumption	23W
	Lumens	2,600/2,800
	Efficacy (LPW)	113/122
	CRI	80+
	Beam	220°
	CCT	3000K, 3500K, 4000K, 5000K
	Life (L70)	50,000 hours
ELECTRICAL	Power Factor	≥0.9
	THD	<20%
	Input Voltage	120-277V
CONSTRUCTION	Operating Temperature	-4°F to 113°F (-20°C to 45°C)
	Base	2G11
LISTINGS	Certification(s)	DesignLights Consortium® Qualified; cULus Listed; FCC
	Material Usage	RoHS Compliant; no mercury or lead
	Environment	UL Listed for damp locations

PERFORMANCE SUMMARY

Order Code	Item #	Lumens	Watts	CCT	CRI	MOL	Base	Life/Hours	Replaces Fluor	DLC
10709	LED23W/PLL/830-G8D	2,600	23W	3000K	80+	22.2"	2G11	50,000	40W CFL PLL	✓
10710	LED23W/PLL/835-G8D	2,600	23W	3500K	80+	22.2"	2G11	50,000	40W CFL PLL	✓
10711	LED23W/PLL/840-G8D	2,800	23W	4000K	80+	22.2"	2G11	50,000	40W CFL PLL	✓
10712	LED23W/PLL/850-G8D	2,800	23W	5000K	80+	22.2"	2G11	50,000	40W CFL PLL	✓

NOTE: Use order code when ordering. ✓DesignLights Consortium Qualified

DIMENSIONS

