

CONNECTORS

Connectors Accessories

Transformer Lug Kits Mechanical Set-Screw Types LK Series



SPECIFICATIONS

- UL486B listed Wire Connector.
- Temperature Rating: 90 °C.
- Voltage: 600V.
- AL9CU.

FEATURES

- Terminal lugs are dual rated for use with both copper and aluminum cables.

CAT. NO.	TRANSFORMER KVA SIZE	QTY.	TERMINAL LUGS INCLUDED		HARDWARE INCLUDED		STD. CTN. QTY.
			LUG TYPE	WIRE RANGE	QTY.	BOLT SIZE	
LK-1	15-37-1/2 1Ø	8	2T	2-14	8	1/4-20X3/4	1
	15-45-3Ø	4	250T	250 MCM-6	8	1/4-20X3/4	1
LK-2	50-75 1Ø	12	250T	250 MCM-6	8	1/4-20 x 3/4	1
	75-112-1/2 3Ø	12	250T	250 MCM-6	8	1/4-20 x 1 3/4	1
LK-3	100-167 1Ø	3	250T	250 MCM-6	3	1/4-20 x 3/4	1
	150-300 3Ø	22	600T	600 MCM-2	16	3/8-16 x 2	1
LK-4	500 3Ø	29	600T	600 MCM-2	18	3/8-16 x 2	1
LK-5	15-25 1Ø	7	0T	1/0-14	7	1/4-20 x 1 1/2	1
	15-37 1/2 3Ø	7	0T	1/0-14	7	1/4-20 x 1 1/2	1
LK-6	37 1/2-50 1Ø	7	250T	250 MCM-6	7	5/16-16 x 1 1/2	1
	45-75 3Ø	6	350T	350 MCM-6	7	5/16-16 x 1 1/2	1
		3	0T	1/0-14	3	1/4-20 x 1	1
LK-7	225 3Ø	6	2-350T	350 MCM-6	6	1/2-13 x 2	1
		6	350T	350 MCM-6	13	3/8-16 x 1 1/2	1
LK-8	225 3Ø	3	500T	500 MCM-4	7	3/8-16 x 2	1
		4	2-600T	600 MCM-2	7	3/8-16 x 2	1
LK-9	300 3Ø	3	2-350T	350 MCM-6	7	1/2-13 x 2	1
		12	500T	500 MCM-4	4	1/2-13 x 2 1/2	1
LK-10	400-500 3Ø	16	800T	800-300 MCM	11	1/2-13 x 2 1/2	1
		3	2-600T	600 MCM-2	11	1/2-13 x 2 1/2	1