



CONNECTOR BLOKS™

Single Primary, Multiple Secondary

AS, AM, AL Series





SPECIFICATIONS

- CSA.
- UL Recognize.

FEATURES

- Each block can stand alone or combine with other blocks to form a multi-block set.
- Add as many holes as you need, in any configuration you want!
- There are no end pieces or connector pieces to fool around with.
- The connector body is made from high strength, high conductivity aluminum alloy and is mounted in a high strength glass-filled polyester base.
- Default SCCR Rating 10,000 Amps.
- Connector Blok™ covers are available in 3 sizes and fits all styles and configurations.



CAT. NO.	FIG. NO.	DRAWING	CONFIGURATION		AMPS PER POLE	LENGTH (L) (IN.)	HEIGHT (W) (IN.)	WIDTH (H) (IN.)	STD. PKG. QTY.	STD. CTN. QTY.
			PRIMARY LINE SIDE	DRAWING						
AS-K1-H4	1		2/0-14 AWG		4-14 AWG	2.900	2.714	1.04	1	3
AS-K1-H6	1		2/0-14 AWG		4-14 AWG	2.900	2.714	1.04	1	3
AM-P1-H6	1		350MCM-6 AWG		4-14 AWG	4.000	2.620	1.710	1	3
AM-P1-H12	1		350MCM-6 AWG		4-14 AWG	4.000	2.620	1.710	1	3
AL-P1-K6	1		350MCM-6 AWG		2/0-14 AWG	5.500	3.250	2.900	1	3
AM-R1-H12	1		500MCM-4 AWG		4-14 AWG	4.000	2.620	1.710	1	3
AL-R1-K6	1		500MCM-4 AWG		2/0-14 AWG	5.500	3.250	2.900	1	3
AL-R1-M4	1		500MCM-4 AWG		4/0-6 AWG	5.500	3.250	2.900	1	3
AL-V1-K6	1		1000-250 MCM		2/0-14 AWG	5.500	3.250	2.900	1	3
ACCESSORIES		CONNECTOR BLOK COVER								STD. CTN. QTY.
CS	2	For use with connector Block AS Series								12
CM	2	For use with connector Block AM Series								9
CL	2	For use with connector Block AL Series								6