



TERMINAL BLOKS™

Hardware Options

FQC, DR Series

SPECIFICATIONS

FQC Series

- Voltage: 30AMP, 600V Max.

DR Series

- CSA.
- UL Recognize.

FEATURES

FQC Series

- Nickel plated.
- 0.250 x 0.30 tab size.
- 22-14AWG wire size.

DR Series

- Made from 35mm unplated 6061-T6 Aluminum alloy providing for a strong, lightweight rail for mounting sockets, terminal blocks or other electro-mechanical devices.
- Comes supplied with oval holes 1.1 cm, approximately x 0.4 cm apart.
- Standard 10mm height allows for ease of installation vs. traditional 7.5mm height.



| CAT. NO. | FIG. NO. | DESCRIPTION | HEIGHT | LENGTH | STD. CTN. QTY. |
|----------|----------|--|--------|--------|----------------|
| FQC-00 | 1 | Quick Disconnect – 0° Flat | – | – | 10 |
| FQC-45 | 2 | Quick Disconnect – 45° Bend | – | – | 10 |
| FQC-90 | 3 | Quick Disconnect – 90° Bend | – | – | 10 |
| J-30 | 4 | 30 AMP Jumper | – | – | 10 |
| DR3910 | 5 | For Mounting Sockets, Terminal Blocks, Or Other Electro-Mechanical Devices | 10 mm | 39.3" | 10 |

TERMINAL BLOKS™

Splicer/Reducers 75 Amps, 600V

TBS Series



SPECIFICATIONS

- Temperature Rating: 150 °C.
- Voltage: 75AMP, 600V Max.

FEATURES

- Terminal Bloks™ power terminal blocks are made from high conductivity bodies and will accept either copper or aluminum conductors on the line side.
- The bases are manufactured from high strength phenolic compound.
- 2-14 AWG.

| CAT. NO. | NO. OF POLES | WIRE RANGE | LENGTH | HEIGHT | WIDTH | STD. CTN. QTY. |
|----------|--------------|-------------------|--------|--------|-------|----------------|
| TBS2-2 | 2 | 2-14 AWG CU or AL | 1.750 | 1.250 | 1.500 | 6 |
| TBS2-3 | 3 | 2-14 AWG CU or AL | 2.380 | 1.250 | 1.500 | 6 |

CONNECTOR BLOKS™