

MINITERMS

Spade Terminals: Locking

S Series

SPECIFICATIONS

- **Vinyl:** Electro tin plated copper, vinyl (PVC) 600V, 75 °C.
- **Un-Insulated:** Electro tin plated copper, 600V, 105 °C.
- **Nylon:** Electro tin plated copper, easy-entry Nylon, 600V, 105 °C.

FEATURES

- Tongue snaps around the screw & terminal is locked into place until the mounting screw can be tightened down.
- Constructed from electro-tin plated copper tubing.
- Available in vinyl, nylon, and un-insulated formats.



FIG. NO.	INSULATION TYPE	WIRE RANGE	STUD SIZE	RATINGS	LENGTH (L) (IN)	WIDTH (W) (IN)	SEAM TYPE	PRO PACKS		STD PACKS		BULK PACKS	
								CAT. NO.	QTY	CAT. NO.	QTY	CAT. NO.	QTY
1	Vinyl	22-18	#10	cULus	0.827	0.315	Butted	–	–	S22-10V-L	100	S22-10V-L-BULK	1000
1	Vinyl	22-18	#6	cULus	0.827	0.228	Butted	–	–	S22-6V-L	100	S22-6V-L-BULK	1000
1	Vinyl	22-18	#8	cULus	0.827	0.315	Butted	–	–	S22-8V-L	100	S22-8V-L-BULK	1000
1	Vinyl	16-14	#10	cULus	0.866	0.335	Butted	S16-10V-L-P	85	S16-10V-L	100	S16-10V-L-BULK	1000
1	Vinyl	16-14	#6	cULus	0.827	0.228	Butted	–	–	S16-6V-L	100	S16-6V-L-BULK	1000
1	Vinyl	16-14	#8	cULus	0.827	0.283	Butted	S16-8V-L-P	85	S16-8V-L	50	S16-8V-L-BULK	1000
1	Vinyl	12-10	#10	cULus	0.992	0.374	Butted	–	–	S12-10V-L	50	S12-10V-L-BULK	500
1	Vinyl	12-10	#6	cULus	0.992	0.335	Butted	–	–	S12-6V-L	50	S12-6V-L-BULK	500
1	Vinyl	12-10	#8	cULus	0.992	0.335	Butted	–	–	S12-8V-L	50	S12-8V-L-BULK	500
2	Un-insulated	22-18	#10	UL	0.694	0.340	Brazed	–	–	S22-10-L	100	S22-10-L-BULK	1000
2	Un-insulated	22-18	#6	UL	0.585	0.260	Brazed	–	–	S22-6-L	100	S22-6-L-BULK	1000
2	Un-insulated	22-18	#8	UL	0.646	0.261	Brazed	–	–	S22-8-L	100	S22-8-L-BULK	1000
2	Un-insulated	16-14	#10	UL	0.694	0.340	Brazed	–	–	S16-10-L	100	S16-10-L-BULK	1000
2	Un-insulated	16-14	#6	UL	0.585	0.260	Brazed	–	–	S16-6-L	100	S16-6-L-BULK	1000
2	Un-insulated	16-14	#8	UL	0.646	0.320	Brazed	–	–	S16-8-L	100	S16-8-L-BULK	1000
2	Un-insulated	12-10	#10	UL	0.773	0.340	Brazed	–	–	S12-10-L	50	S12-10-L-BULK	1000
2	Un-insulated	12-10	#6	UL	0.664	0.260	Brazed	–	–	S12-6-L	50	S12-6-L-BULK	1000
2	Un-insulated	12-10	#8	UL	0.646	0.261	Brazed	–	–	S12-8-L	50	S12-8-L-BULK	1000
3	Nylon	22-18	#8	UL	0.866	0.315	Butted	–	–	S22-8N-L	100	S22-8N-L-BULK	1000
3	Nylon	16-14	#10	UL	0.906	0.335	Butted	–	–	S16-10N-L	100	S16-10N-L-BULK	1000
3	Nylon	16-14	#6	UL	0.866	0.328	Butted	–	–	S16-6N-L	100	S16-6N-L-BULK	1000
3	Nylon	16-14	#8	UL	0.866	0.283	Butted	–	–	S16-8N-L	100	S16-8N-L-BULK	1000
3	Nylon	12-10	#10	UL	1.012	0.374	Butted	–	–	S12-10N-L	50	S12-10N-L-BULK	1000
3	Nylon	12-10	#8	UL	1.012	0.335	Butted	–	–	S12-8N-L	50	S12-8N-L-BULK	1000