

# MINITERMS

## Uninsulated Ring Terminals

R Series

### SPECIFICATIONS

- Un-Insulated Electro fin plated copper, 600V, 105 °C.

### FEATURES

- Uninsulated Ring Terminal have Basic tongue type ring terminal. Safe and reliable connections, because it cannot be disconnected unless the screw is completely removed.



FIG. NO.	INSULATION TYPE	WIRE RANGE	STUD SIZE	RATINGS	LENGTH (L) (IN.)	WIDTH (W) (IN.)	SEAM TYPE	PRO PACKS		STD PACKS		BULK PACKS	
								CAT. NO.	QTY	CAT. NO.	QTY	CAT. NO.	QTY
1	Un-insulated	22-18	1/4	UL	0.894	0.255	Brazed	—	—	R22-14	100	R22-14-BULK	1000
1	Un-insulated	22-18	5/16	UL	0.893	0.323	Brazed	—	—	R22-56	100	R22-56-BULK	1000
1	Un-insulated	22-18	3/8	UL	1.097	0.38	Brazed	—	—	R22-38	100	R22-38-BULK	1000
1	Un-insulated	22-18	#10	cULus	0.629	0.314	Brazed	—	—	R22-10	100	R22-10-BULK	1000
1	Un-insulated	22-18	#6	UL	0.702	0.312	Brazed	—	—	R22-6	100	R22-6-BULK	1000
1	Un-insulated	22-18	#8	cULus	0.629	0.314	Brazed	—	—	R22-8	100	R22-8-BULK	1000
2	Un-insulated	16-14	1/4	cULus	0.866	0.472	Brazed	—	—	R16-14	100	R16-14-BULK	1000
2	Un-insulated	16-14	5/16	UL	0.892	0.472	Brazed	—	—	R16-56	100	R16-56-BULK	1000
2	Un-insulated	16-14	3/8	cULus	1.011	0.535	Brazed	—	—	R16-38	100	R16-38-BULK	1000
2	Un-insulated	16-14	1/2	—	1.123	0.748	Brazed	—	—	R16-50	100	R16-50-BULK	1000
2	Un-insulated	16-14	#10	cULus	0.669	0.334	Brazed	R16-10-P	125	R16-10	100	R16-10-BULK	1000
2	Un-insulated	16-14	#6	UL	0.704	0.313	Brazed	—	—	R16-6	100	R16-6-BULK	1000
2	Un-insulated	16-14	#8	cULus	0.669	0.334	Brazed	R16-8-P	125	R16-8	100	R16-8-BULK	1000
3	Un-insulated	12-10	1/4	cULus	0.885	0.472	Brazed	—	—	R12-14	50	R12-14-BULK	1000
3	Un-insulated	12-10	5/16	cULus	1.07	0.59	Brazed	—	—	R12-56	50	R12-56-BULK	500
3	Un-insulated	12-10	3/8	cULus	1.07	0.59	Brazed	—	—	R12-38	50	R12-38-BULK	500
3	Un-insulated	12-10	1/2	—	1.284	0.755	Brazed	—	—	R12-50	50	R12-50-BULK	500
3	Un-insulated	12-10	#10	cULus	0.74	0.372	Brazed	R12-10-P	80	R12-10	50	R12-10-BULK	1000
3	Un-insulated	12-10	#6	UL	0.766	0.374	Brazed	—	—	R12-6	50	R12-6-BULK	500
3	Un-insulated	12-10	#8	UL	0.766	0.376	Brazed	—	—	R12-8	50	R12-8-BULK	500
4	Un-insulated	8	1/4	UL	0.956	0.457	Brazed	—	—	R8-14	50	R8-14-BULK	500
4	Un-insulated	8	5/16	UL	0.952	0.471	Brazed	—	—	R8-56	50	R8-56-BULK	500
4	Un-insulated	8	3/8	UL	1.083	0.59	Brazed	—	—	R8-38	50	R8-38-BULK	500
4	Un-insulated	8	#10	UL	0.955	0.47	Brazed	—	—	R8-10	50	R8-10-BULK	500
5	Un-insulated	#6	1/4	UL	1.253	0.634	Brazed	—	—	R6-14	50	R6-14-BULK	500
5	Un-insulated	#6	5/16	UL	1.243	0.635	Brazed	—	—	R6-56	50	R6-56-BULK	500
5	Un-insulated	#6	3/8	UL	1.239	0.635	Brazed	—	—	R6-38	50	R6-38-BULK	500
5	Un-insulated	#6	1/2	UL	1.434	0.827	Brazed	—	—	R6-50	50	R6-50-BULK	500
5	Un-insulated	#6	#10	UL	1.18	0.485	Brazed	—	—	R6-10	50	R6-10-BULK	500
6	Un-insulated	#4	1/4	UL	1.245	0.469	Brazed	—	—	R4-14	25	R4-14-BULK	500
6	Un-insulated	#4	5/16	UL	1.25	0.476	Brazed	—	—	R4-56	25	R4-56-BULK	500
6	Un-insulated	#4	3/8	UL	1.34	0.665	Brazed	—	—	R4-38	25	R4-38-BULK	500
6	Un-insulated	#4	1/2	UL	1.327	0.665	Brazed	—	—	R4-50	25	R4-50-BULK	500
7	Un-insulated	#2	1/4	UL	1.563	0.636	Brazed	—	—	R2-14	25	R2-14-BULK	500
7	Un-insulated	#2	5/16	UL	1.673	0.868	Brazed	—	—	R2-56	25	R2-56-BULK	500
7	Un-insulated	#2	3/8	UL	1.563	0.635	Brazed	—	—	R2-38	25	R2-38-BULK	500
7	Un-insulated	#2	1/2	UL	1.677	0.868	Brazed	—	—	R2-50	25	R2-50-BULK	500