




WIRE MANAGEMENT

Narrow Finger, High Density Panel Channel

PC-LSN Series




SPECIFICATIONS

- CSA and UL Recognized.
- Tested to UL File up to 50 °C (122 °F). 94V-0 rated.
- Maximum Service Temperature: 85 °C (185 °F).




FEATURES

- Narrower finger width is 6mm.
- Slot width is 4mm.
- Made from high-impact, self-extinguishing, warp-proof PVC.
- Optional adhesive backing is available.
- 5mm slot width is available in both white and grey for 1020, 2020, 2030, 2040

Mounting holes: For widths up to 2.5"



Mounting holes: For widths over 2.5"



CAT. NO.	COLOR	NOMINAL SIZE	LENTH (FT.)	STD. PKG. QTY.	STD. CTN. QTY.
PC.75.75-LSN	Grey	3/4 x 3/4	6'	6'	72'
PC1010-LSN	Grey	1 x 1	6'	6'	72'
PC1010-LSN-W	White	1 x 1	6'	6'	72'
PC1015-LSN	Grey	1 x 1 1/2	6'	6'	72'
PC1015-LSN-W	White	1 x 1 1/2	6'	6'	72'
PC10175-LSN	Grey	1 x 1 3/4	6'	6'	72'
PC10175-LSN-W	White	1 x 1 3/4	6'	6'	72'
PC1020-LSN	Grey	1 x 2	6'	6'	72'
PC1020-LSN-W	White	1 x 2	6'	6'	72'
PC10250-LSN	Grey	1 x 2 1/2	6'	6'	72'
PC1030-LSN	Grey	1 x 3	6'	6'	72'
PC1030-LSN-W	White	1 x 3	6'	6'	72'
PC1515-LSN	Grey	1 1/2 x 1 1/2	6'	6'	72'
PC1520-LSN	Grey	1 1/2 x 2	6'	6'	72'
PC1520-LSN-W	White	1 1/2 x 2	6'	6'	72'
PC1530-LSN	Grey	1 1/2 x 3	6'	6'	72'
PC1540-LSN	Grey	1 1/2 x 4	6'	6'	72'
PC175175-LSN	Grey	1 3/4 x 1 3/4	6'	6'	72'
PC2020-LSN	Grey	2 x 2	6'	6'	72'
PC2020-LSN-W	White	2 x 2	6'	6'	72'
PC2030-LSN	Grey	2 x 3	6'	6'	72'
PC2030-LSN-W	White	2 x 3	6'	6'	72'
PC2040-LSN	Grey	2 x 4	6'	6'	72'
PC3020-LSN	Grey	3 x 2	6'	6'	72'
PC3020-LSN-W	White	3 x 2	6'	6'	72'
PC3030-LSN	Grey	3 x 3	6'	6'	72'
PC3040-LSN	Grey	3 x 4	6'	6'	72'
PC4020-LSN-W	White	4 x 2	6'	6'	72'
PC4030-LSN	Grey	4 x 3	6'	6'	72'
PC4040-LSN	Grey	4 x 4	6'	6'	72'