

WIRE MANAGEMENT

Self Sealing UP Splice Kit & Hot Melt Sealant Sleeves

Easy-Splice™
SKSS, HMSS Series



SPECIFICATIONS

- UL Listed and CSAus.
- **Installation (SKSS):** Use a minimum of one sleeve for every two cable conductors. Install HWHS or CRS product over HMSS sealant sleeves to melt sealant sleeves and provide cable block.

FEATURES

Self Healing (SKSS)

- Fully waterproof, submersible and re-enterable splice, through the use of uniquely designed interference fit covers.
- Kit comes complete with a connector, silicone and cover. AWG UF cable.

Hot Melt Sealing (SKSS)

- Used to provide a cable block in multi-conductor cables.



CAT. NO.	CERTIFICATION	FIG. NO.	NO. OF SLEEVES/CONDUCTORS	LENGTH (IN.)	INSIDE DIA. (IN.)	WIRERANGE (IN.)	CONNECTOR LENGTH (IN.)	STD. CTN. QTY.
SKSS-2	UL	1	2	—	—	14/2-10/2	9.500	12
SKSS-3	UL	2	3	—	—	14/3-10/3	9.500	12
HMSS-4-40	—	3	#24 — #20 AWG: Use 1 Sleeve/2 Conductors	1.75	0.160	—	—	100
HMSS-4-40	—	3	#14 — #12 AWG: Use 1 Sleeve/Conductor	1.75	0.160	—	—	100