

# WIRE MANAGEMENT

## Heavy Wall Heat Shrink for Direct Burial & Submersible

### Easy-Splice™

#### HWHS Series Cnt'd



#### SPECIFICATIONS

- UL 486D Listed and CSA C22.2.
- **Temperature Rating:** 121-135 °C, 1000V.
- **Application:** Qualified to ANSI C119.1-1986 for underground splicing. Insulate and seal buried electrical connections rated up to 1,000 volts.
- **Connectors Up To 6 Inches:** Recommended cut length = Connector length + 4 inches.
- **Connectors Over 6 Inches:** Recommended cut length = Connector length + 5 inches.

#### FEATURES

- Made of specially formulated polyolefin irradiated and thermally stabilized to give the material "elastic memory".
- When a proper amount of heat is directly applied to the shrink sleeve, it will permanently shrink to its original unexpanded diameter tightly cover and "mold" itself into irregular shapes.
- The interior of the sleeve is coated with an adhesive that assures a watertight seal after shrinking.
- For use on standard poly- or elastomeric-insulated/jacketed cables or lead-jacketed cables, which may include aluminum or steel armoring.
- RUS accepted for use as a secondary tap or splice cover. May be used for jacket repair on cables up to 35 kV.

CAT. NO.	SEALABLE WIRE RANGE	LENGTH (IN.)	GENERAL USE RANGE (IN.)		MAX. CONNECTOR O.D. (IN.)	MIN. SEAL LENGTH PER SIDE (IN.)	STD. PKG. QTY.
			RECOVERED	EXPANDED			
HWHS20-750-6	2/0 AWG - 750 MCM	6	0.510	1.730	1.300	2.000	3
HWHS20-750-9	2/0 AWG - 750 MCM	9	0.510	1.730	1.300	2.000	3
HWHS20-750-12	2/0 AWG - 750 MCM	12	0.510	1.730	1.300	2.000	3
HWHS20-750-48	2/0 AWG - 750 MCM	48	0.510	1.730	1.300	2.000	3
HWHS250-1000-6	250-1000 MCM	6	0.700	1.960	1.500	2.000	3
HWHS250-1000-9	250-1000 MCM	9	0.700	1.960	1.500	2.000	3
HWHS250-1000-12	250-1000 MCM	12	0.700	1.960	1.500	2.000	3
HWHS250-1000-48	250-1000 MCM	48	0.700	1.960	1.500	2.000	3
HWHS500-1500-9	500-1500 MCM	9	0.860	2.480	1.840	2.500	3
HWHS500-1500-12	500-1500 MCM	12	0.860	2.480	1.840	2.500	3
HWHS500-1500-48	500-1500 MCM	48	0.860	2.480	1.840	2.500	3
HWHS800-2000-12	800-2000 MCM	12	1.290	3.930	—	2.500	3
HWHS800-2000-48	800-2000 MCM	48	1.290	3.930	—	2.500	3
HWHS1500-2500-12	1500-2500 MCM	12	1.490	4.640	—	2.500	3
HWHS1500-2500-48	1500-2500 MCM	48	1.490	4.640	—	2.500	3