

WIRE MANAGEMENT

Oxide Inhibitor & Duct Sealing Compound

Inhibitors
OX, DS Series

FEATURES

Oxide Inhibitor (OX)

- Universal oxide inhibitor for aluminum and/or copper terminations.
- Remains stable over a wide temperature range.
- Supplied in clear, easy-squeeze bottles or tubes.

Duct Sealing Compound (DS)

- Intended for sealing around electrical service entries, junction boxes and other devices where weather-proofing is critical.
- Will stay soft and pliable for several years and has an excellent shelf life.
- Will not damage wire covers, glass, wood, painted surfaces, plastics or other materials it may contact.
- It is chemically inert, inhibiting no chemical activity and is nontoxic.
- Contains no asbestos or mineral fibers and no mineral oil which can shorten the effective life of the product.
- Remains pliable through a wide range of temperatures and will adhere to most clean dry surfaces.



| CAT. NO. | CERTIFICATION | FIG. NO. | DESCRIPTION | SIZE (OZ) | STD. CTN. QTY. |
|----------|---------------|----------|----------------------------------|-----------|----------------|
| OX-8 | — | 1 | Oxide Inhibitor. Squeeze Bottle. | 8 oz. | 12 |
| OX-4 | — | 2 | Oxide Inhibitor. Squeeze Bottle. | 4 oz. | 12 |
| OX-1 | — | 3 | Oxide Inhibitor. Squeeze Tube. | 3/4 oz. | 100 |
| DS184 | UL | 4 | Duct Seal — 1 Lb. Pkg. | — | 50 |
| DS185 | UL | 5 | Duct Seal — 5 Lbs. Pkg. | — | 10 |