

CABLE TIES

Standard (Natural) Cable Ties

Standard - Natural Series



SPECIFICATIONS

- cULus Listed for Positioning Devices. UL62275.
- **Temperature Rating:** Min., -40°F to Max., 185°F (-40°C to 85°C)
- **Ideal Storage:** 23°C, Humidity 50%, Avoid storing cable ties next to warm objects.
- **Type 21 AH-2:** "Suitable for use in air-handling spaces (Plenums)".

FEATURES

- Designed for quick and easy use.
- Strong and flexible, they can be wrapped around a bundle quickly and the tail is easily inserted into a self-locking head.
- The smaller standard size ties have bent tails to facilitate insertion by user.
- Made of high-strength Nylon 66 that resists abrasion and chemicals such as common oils, greases, solvents, dilute acids and alkalines.
- Fungus-resistant, self-extinguishing and have excellent dielectric properties.

CAT. NO.	MAX. WIRE/CABLE SIZE (L)	MAX BUNDLE DIAMETER	TENSILE STRENGTH	LENGTH (IN.)	WIDTH (IN.)	STD. PKG. QTY.	STD. CTN. QTY.
418	4"	0.800	18 Lbs.	4.000	0.095	100	5,000
418X	4"	0.800	18 Lbs.	4.000	0.095	1000	5,000
450	4"	0.800	50 Lbs.	4.750	0.095	100	5,000
518	5"	1.430	18 Lbs.	5.500	0.095	100	5,000
518X	5"	1.375	18 Lbs.	5.500	0.100	1000	5,000
540	5"	1.300	40 Lbs.	5.500	0.140	100	3,000
540X	5"	1.300	40 Lbs.	5.500	0.140	1000	3,000
650	6"	1.320	50 Lbs.	6.250	0.181	100	3,000
650X	6"	1.320	50 Lbs.	6.250	0.181	1000	3,000
750	7"	1.810	50 Lbs.	7.500	0.189	100	3,000
750X	7"	1.810	50 Lbs.	7.500	0.189	1000	3,000
818	8"	2.060	18 Lbs.	8.000	0.095	100	3,000
818X	8"	2.060	18 Lbs.	8.000	0.095	1000	3,000
840	8"	2.060	40 Lbs.	8.000	0.140	100	3,000
840X	8"	2.060	40 Lbs.	8.000	0.140	1000	3,000
850	8"	1.940	50 Lbs.	8.000	0.189	100	3,000
850X	8"	1.940	50 Lbs.	8.000	0.189	1000	3,000
875	8"	1.940	75 Lbs.	8.000	0.189	100	3,000
8120	8"	2.000	120 Lbs.	8.000	0.300	100	2,000
8120X	8"	2.000	120 Lbs.	8.000	0.300	1000	2,000