

CABLE TIES

Air Handling & Push Mount Cable Ties

-P, -PM Series

FEATURES

Air Handling (-P)

- Air handling ties are approved for indoor use in air handling spaces other than plenums and ducts per NFPA-1993.
- Made of high strength nylon, these ties are self-extinguishing and resist abrasions and chemicals such as oil, greases, solvents, dilute acids and alkalies.
- Burgundy in color for easy identification.

Push Mount (-PM)

- Secure a cable tie to a back panel quickly and easily, eliminating the possibility of adhesive mount failure.
- Drill the mounting hole and insert.
- Made of high-strength Nylon 66 that resists abrasion and chemicals such as common oils, greases, solvents, dilute acids and alkalines.
- Fungus-resistant, self-extinguishing and excellent dielectric properties.

SPECIFICATIONS

- UL Listed and CSA (-P).
- Meets UL62275 test standards. MIL spec. 3367-1, -7, -2. NEC Sec. 300-22 (C) & (D), Rules 12-010 (3), (4), and (5) and 12-020 of the Canadian Electrical code, Part 1.
- **Temperature Rating (-P):** Maximum operating temperature 85 °C (185 °F).
- **Temperature Rating (-PM):** -40 °C to 85 °C (-40 °F to 185 °F) and will withstand temperatures up to 149 °C (300.2 °F). 94V-2 flammability rating.



CAT. NO.	CERTIFICATION	MAX. WIRE/ CABLE SIZE	MAX. BUNDLE DIA.	MIN. TENSILE STRENGTH	MTG. HOLE SIZE REQ. (IN.)	LENGTH (IN.)	WIDTH (IN.)	STD. PKG. QTY.	STD. CTN. QTY.
750-P	UL/CSA	7"	1.750	50 Lbs.	—	7.500	0.180	100	5,000
1150-P	UL/CSA	11"	3.000	50 Lbs.	—	11.100	0.180	100	5,000
1450-P	UL/CSA	14"	4.000	50 Lbs.	—	14.200	0.180	100	5,000
640-PM	UL Recognized	6"	1.59	40 Lbs.	3/16	6.125	0.139	100	1,000