

CABLE TIES

Standard Fluorescent Ties

SPECIFICATIONS

- cULus Listed for Positioning Devices UL62275.
- **Temperature Rating:** Min., -40°F to Max., 185°F (-40°C to 85°C).
- **Type 21 AH-2:** "Suitable for use in air-handling spaces (Plenums)".

FEATURES

- Designed for quick and easy use.
- Strong and flexible, they can be wrapped around a bundle quickly and the tail is easily inserted into a self-locking head.
- The smaller standard size ties have bent tails to facilitate insertion by user.
- Made of high-strength Nylon 66 that resists abrasion and chemicals such as common oils, greases, solvents, dilute acids and alkalines.
- Fungus-resistant, self-extinguishing and have excellent dielectric properties.



CAT. NO.	FIG. NO.	COLOR (FLOURESCENT)	MAX. WIRE/CABLE SIZE	MAX BUNDLE DIAMETER	TENSILE STRENGTH	LENGTH (IN.)	WIDTH (IN.)	STD. PKG. QTY.	STD. CTN. QTY.
750-16	1	Orange	7"	1.750	50 Lbs.	7.500	0.187	100	3,000
750-18	2	Green	7"	1.810	50 Lbs.	7.500	0.189	100	3,000
750-20	3	Blue	7"	1.810	50 lbs.	7.500	0.189	100	3,000
840-11	4	Pink	8"	2.000	40 Lbs.	8.500	0.130	100	3,000
840-16	1	Orange	8"	2.000	40 Lbs.	8.500	0.130	100	3,000
840-17	5	Yellow	8"	2.060	40 Lbs.	8.000	0.140	100	3,000
840-18	2	Green	8"	2.000	40 Lbs.	8.500	0.130	100	3,000
840-20	3	Blue	8"	2.000	40 Lbs.	8.500	0.130	100	3,000
1150-11	4	Pink	11"	3.000	50 Lbs.	11.100	0.187	100	2,000
1150-16	1	Orange	11"	3.000	50 Lbs.	11.100	0.187	100	2,000
1150-17	5	Yellow	11"	3.000	50 Lbs.	11.100	0.187	100	2,000
1150-18	2	Green	11"	3.000	50 Lbs.	11.100	0.187	100	2,000
1150-20	3	Blue	11"	3.000	50 Lbs.	11.100	0.187	100	2,000