

# CABLE TIES

## Push Mounts

### SM Series

### SPECIFICATIONS


- Temperature Rating: -80 °C to 538 °C (-112 °F to 1000.4 °F).

### FEATURES

- Manufactured using UL approved Nylon 66, 94V-2.
- Saddle design provides maximum stability to wire bundles.




Figure 1



SM-0, 0L

Figure 2



SM-1, 2, 3

CAT. NO.	FIG. NO.	COLOR	SCREW SIZE	SLOT WIDTH	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	STD. PKG. QTY.	STD. CTN. QTY.
SM-0	1	Natural	0.133	0.200	0.750	0.370	0.200	100	1,000
SM-0L	1	Natural	0.204	0.200	0.750	0.370	0.200	100	1,000
SM-1	2	Natural	0.120	0.280	0.590	0.390	0.280	100	1,000
SM-2	2	Natural	0.130	0.160	0.500	0.280	0.230	100	1,000
SM-3	2	Natural	0.236	0.350	0.900	0.630	0.350	100	1,000
SM-1-B	2	Black	0.120	0.280	0.590	0.390	0.280	100	1,000
SM-2-B	2	Black	0.130	0.160	0.500	0.280	0.230	100	1,000
SM-3-B	2	Black	0.236	0.350	0.900	0.630	0.350	100	1,000