

**MINITERMS**

**High Temperature  
Spade, Ring, Piggyback  
& Disconnect  
HT SERIES**

**FEATURES**

**UN-INSULATED:**

Spade style terminal, Nickel plated copper, brazed seam, 900 °F

**UN-INSULATED:**

Ring style terminal, Nickel plated copper, brazed seam, 900 °F

**UN-INSULATED:**

Turned up edges give this spade more safety and reliability.

**UN-INSULATED:**

Male disconnect

**UN-INSULATED:**

Female flag style terminal

**UN-INSULATED:**

Similar tongue style to a spade, block spades have longer, flatter sides designed for use in terminal blocks.

Female quick disconnect with brazed seam, 600V, 105 °C.



STYLE	INSULATION TYPE	WIRE RANGE	STUD SIZE	CERTIFICATION VARIANCE
Spade	Un-insulated	12-10	#10	
Ring	Un-insulated	22-18	#10	UL
Ring	Un-insulated	22-18	#6	NON-UL
Ring	Un-insulated	22-18	#8	UL
Ring	Un-insulated	16-14	#10	UL
Ring	Un-insulated	16-14	#6	UL
Ring	Un-insulated	16-14	#8	UL
Ring	Un-insulated	12-10	1/4	NON-UL
Ring	Un-insulated	12-10	#10	UL
Ring	Un-insulated	12-10	#8	NON-UL
Piggyback	Un-insulated	16-14	0.250	
Disconnect Male	Un-insulated	12-10	0.250	
Disconnect Female Flag	Un-insulated	16-14	0.250	
Disconnect Female Flag	Un-insulated	12-10	0.250	
Disconnect Female	Un-insulated	16-14	0.250	
Disconnect Female	Un-insulated	12-10	0.250	
Disconnect Female	Un-insulated	8	0.250	

MINITERMS



		<b>"S" PACKS</b>		<b>PRO PACKS</b>		<b>STD PACKS</b>		<b>BULK PACKS</b>	
L (IN)	W (IN)	CAT. NO.	QTY	CAT. NO.	QTY	CAT. NO.	QTY	CAT. NO.	QTY
0.499	0.384	<b>HTS12-10-S</b>	15	–	–	–	–	<b>HTS12-10-BULK</b>	1000
0.443	0.325	–	–	–	–	<b>HTR22-10</b>	100	<b>HTR22-10-BULK</b>	1000
0.443	0.270	–	–	–	–	<b>HTR22-6</b>	100	<b>HTR22-6-BULK</b>	1000
0.411	0.270	–	–	–	–	<b>HTR22-8</b>	100	<b>HTR22-8-BULK</b>	1000
0.450	0.384	–	–	<b>HTR16-10-P</b>	100	<b>HTR16-10</b>	100	<b>HTR16-10-BULK</b>	1000
0.470	0.345	–	–	–	–	<b>HTR16-6</b>	100	<b>HTR16-6-BULK</b>	1000
0.444	0.390	–	–	–	–	<b>HTR16-8</b>	100	<b>HTR16-8-BULK</b>	1000
0.616	0.482	–	–	–	–	<b>HTR12-14</b>	50	<b>HTR12-14-BULK</b>	1000
0.530	0.384	–	–	<b>HTR12-10-P</b>	60	<b>HTR12-10</b>	50	<b>HTR12-10-BULK</b>	1000
0.530	0.384	–	–	–	–	<b>HTR12-8</b>	50	<b>HTR12-8-BULK</b>	1000
0.625	0.291	–	–	–	–	<b>HTP16-250-3</b>	–	<b>HTP16-250-3-BULK</b>	1000
0.685	0.250	–	–	–	–	<b>HTM12-250-3</b>	50	<b>HTM12-250-3-BULK</b>	1000
0.506	0.312	–	–	<b>HTSF16-250-3-P</b>	60	<b>HTSF16-250-3</b>	60	<b>HTSF16-250-3-BULK</b>	1000
0.587	0.294	–	–	<b>HTSF12-250-3-P</b>	50	<b>HTSF12-250-3</b>	50	<b>HTSF12-250-3-BULK</b>	1000
0.500	0.250	<b>HTF16-250-3-S</b>	15	<b>HTF16-250-3-P</b>	60	<b>HTF16-250-3</b>	50	<b>HTF16-250-3-BULK</b>	1000
0.690	0.304	<b>HTF12-250-3-S</b>	15	–	–	–	–	<b>HTF12-250-3-BULK</b>	500
0.715	0.304	–	–	<b>HTF8-250-3-P</b>	–	<b>HTF8-250-3</b>	25	<b>HTF8-250-3-BULK</b>	1000