

DIGITAL

Auto OFF Countdown Timer

Residential In-Wall

D Series



SPECIFICATIONS

- Timing Accuracy: Line voltage.
- Wire Size: #14AWG
- Operating Temperature: 32 °F to 122 °F (0 °C to 50 °C).

WIRING DIAGRAMS

- See Pages 377-388 For Diagrams.

APPLICATIONS

- Whole house fans, Indoor/Outdoor lighting.
- Bathroom fans and lights, self storage.

FEATURES

- **Variable Timing:**
 - Button push changes time ON setting.
 - D1060M: 10, 20, 30, 60 minute.
 - D212H: 2, 4, 8, 12 hour.
- **LED Display:** Indicator moves to new range as timer counts down.
- **Tamper Resistant:** Time ON interval preset.
- **Easy Set:** No adjustments, just wire and go!
- **Wiring:** Requires a neutral.
- **Colors:** Ivory, Light Almond, White.

CAT. NO.	COLOR	CERTIFICATION	UPC CODE	SUPPLY VOLTAGE VAC 50/60Hz	TIME SETTINGS	GENERAL PURPOSE	RATINGS			
							RESISTIVE	TUNGSTEN	BALLAST	MOTOR
D212H	Ivory	cULus	14021	120	2, 4, 8, 12 Hours	15A	1000W	1000W	1000VA	1/4HP
D212HA	Light Almond	cULus	14022	120	2, 4, 8, 12 Hours	15A	1000W	1000W	1000VA	1/4HP
D212HW	White	cULus	14023	120	2, 4, 8, 12 Hours	15A	1000W	1000W	1000VA	1/4HP
D1060M	Ivory	cULus	14025	120	10, 20, 30, 60 Minutes	15A	1000W	1000W	1000VA	1/4HP
D1060LA	Light Almond	cULus	14024	120	10, 20, 30, 60 Minutes	15A	1000W	1000W	1000VA	1/4HP
D1060MW	White	cULus	14026	120	10, 20, 30, 60 Minutes	15A	1000W	1000W	1000VA	1/4HP

TORK® DIGITAL PRODUCTS