

TORKALERT™

Warning Lights

Industrial Units



APPLICATIONS

- 1/2" conduit mounting. Full selection of dome colors. For outdoor use. All units must be mounted vertically with base at bottom.

FEATURES

- **All Purpose 360° Beacon:** Large parabolic reflector rotates around a 100 watt bulb. Long range beam. Use to indicate equipment malfunctions, security intrusion, etc..
- **Midi-Strobe:** Solid state circuitry in a low profile design. No moving parts means less Maintenance!
- **Compact Rotating Beacon:** Light intensifying reflector rotates around a low current 25 watt bulb. Bayonet socket for easy lamp replacement. Ideal for restricted or dangerous areas.
- **Electronic Strobe:** High intensity strobe tube with inner fluted lens for maximum brilliance. No moving parts makes it immune to shock and vibration. Ideal for security alert.
- **Color:** Red (R), Amber (A), Clear (C) and Blue (B).



| CAT. NO. | FIG. NO. | CERTIFICATION | TYPE | UPC CODE | DESCRIPTION | INPUT VOLTAGE | AMPS |
|-----------|----------|---------------|-------------------------|----------|---|---------------|------|
| TA47RN5 | 1 | — | All Purpose 360° Beacon | 96061 | 90 FPM. Corrosion resistant/Outdoor use. Glass filled polypropylene housing Acrylic dome. Tamper resistant dome clamps. Nominal current draw 9 1/2"H x 8 1/2" diameter. | 117VAC | .9 |
| TA47AN5 | 1 | — | All Purpose 360° Beacon | 96161 | | 117VAC | |
| TA93-2RN5 | 2 | — | Midi-Strobe | 99622 | 70-80 FPM. Solid state electronic circuitry. High output 3-4 watt, 3.6 joules Vertically mounted flash tube. Snap out socket base for 360° Fresnel dome optics. Nominal current draw 6 1/2"H x 5 1/8" diameter. | 117VAC | .04 |
| TA93-2AN5 | 2 | — | Midi-Strobe | 97623 | | | |
| TA93-2CN5 | 2 | — | Midi-Strobe | 96968 | | | |
| TA93-2BN5 | 2 | — | Midi-Strobe | 97624 | | | |
| TA52RN5 | 3 | UL | Compact Rotating Beacon | 96063 | 80-90 FP. 360° rotation. Dependable belt & turntable design. Acrylic dom. Nominal current draw 6 1/2"H x 55/8" diameter. | 117VAC | .21 |
| TA52AN5 | 3 | UL | Compact Rotating Beacon | 96163 | | | |
| TA52BN5 | 3 | UL | Compact Rotating Beacon | 96263 | | | |
| TA94RN5 | 4 | — | Electronic Strobe | 97626 | 70-80 FPM. Solid state electronic circuitry High output 3-4 watt, 3.6 joules. Acrylic dome. Glass filled polypropylene housing. Suitable for outdoor use 9 1/2"H x 8 1/2" diameter. | 117VAC | .04 |
| TA94AN5 | 4 | — | Electronic Strobe | 97627 | | | |
| TA94BN5 | 4 | — | Electronic Strobe | 97628 | | | |