

POOL & SPA

Digital Two-Speed Pump Timers

TPX Series

APPLICATIONS

- Swimming pool and spa lighting.
- Submersible fixtures.
- Landscape lighting.
- Fountain lighting.

FEATURES

- Low Voltage:** Designed for the safe operation of 12 volt lighting loads including no niche fixtures.
- Pool & Spa:** 100 watt unit for outdoor use only. 300 and 600 watt units for indoor or outdoor use.
- Landscape Lighting:** 100 watt unit for outdoor use only. 300 and 600 watt units for indoor or outdoor use.
All units for outdoor use only in Canada.
- Safe Operation:** Full ground shield between primary and secondary.
- Overload Protection:** Automatic resetting internal overload protection.



SPECIFICATIONS

- Input Voltage:** 120 or 240VAC, 60Hz.
- Output Voltage:**
 - TPX100(S): 12 & 13 VAC, 100 Watts max.
 - TPS300(S): 12, 13, & 14 VAC, 300 Watts max.
 - TPX600: 12, 13, & 14 VAC, 2 x 300 Watts max.
- Color:** Grey or Stainless Steel.
- Enclosure Size:**
 - TPX100(S) and TPX300(S) 7.2 H x 5.1 W x 4.2 D inches.
 - TPX600 10.4 H x 7.3 W x 4.2 D inches.



| CAT. NO. | UPC CODE | INPUT SUPPLY 60Hz | OUTPUT CONTACTS |
|----------|----------|-----------------------|-----------------|
| TPX100 | 94052 | 120VAC 1 AMP Max. | Painted Steel |
| TPX100S | 94053 | 120VAC 1 AMP Max. | Stainless Steel |
| TPX300 | 94054 | 120VAC 3 AMP Max. | Painted Steel |
| TPX300S | 94055 | 120VAC 3 AMP Max. | Stainless Steel |
| TPX600 | 94056 | 120VAC 2 x 3 AMP Max. | Painted Steel |