


CONNECTORS

Compression Connectors

Dual Rated, Wide Range Tap Connectors
WRD Series Cont'd



SPECIFICATIONS

- Voltage: 600V.

FEATURES

- For combinations of aluminum and aluminum-copper conductors.
- Standard compression tools and dies install all sizes.
- Formable ribs provide broader contact area.
- Fold-in tabs provide positive tab interlock as tool closes.
- Made from high strength aluminum alloy.
- All connectors are reversible.

FOR TOOL/DIE CRIMPING INFORMATION,
PLEASE SEE TABLE ON PAGE 92

CAT. NO.	STANDARD CONDUCTOR RANGE						COMPACT CONDUCTOR				STD. CTN. QTY.
	A GROOVE			B GROOVE			A GROOVE		B GROOVE		
	ACSR	STR	SOL	ACSR	STR	SOL	ACSR	STR	ACSR	STR	
WRD9	-	-	1	-	8	8	-	-	-	-	50
	3	2	2	-	10	10	-	-	-	-	50
	4	3	3	-	12	12	-	-	-	-	50
	6	4	4	-	14	14	-	-	-	-	50
	6	-	-	-	-	-	-	-	-	-	50
WRD139	-	2/0	-	-	-	-	-	-	-	-	25
	1/0	1/0	-	-	-	-	-	-	-	-	25
	1	1	1	-	-	6	-	-	-	-	25
	2	2	2	-	-	-	-	-	-	-	25
	3	3	-	-	10	10	-	-	-	-	25
WRD149	4	-	-	-	-	-	-	-	-	-	25
	-	-	2	-	-	2	-	2	-	2	25
	-	3	3	-	3	3	-	3	3	3	25
	4	4	4	4	4	4	4	4	4	4	25
WRD179	6	6	6	6	6	6	6	6	6	6	25
	1/0	1/0	-	-	-	2	-	2/0	-	2	25
	1	1	1	-	3	3	1/0	1/0	-	3	25
	2	2	-	4	4	4	1	1	4	4	25
WRD199	3	-	-	6	6	6	2	2	6	6	25
	1/0	1/0	-	-	1	1	-	2/0	1	1	25
	1	1	1	2	2	2	1/0	1/0	2	2	25
	2	2	-	3	3	-	1	1	3	-	25
WRD219	3	-	-	4	4	-	2	2	4	-	25
	1/0	1/0	-	1/0	1/0	-	-	2/0	-	2/0	25
	1	1	-	1	1	-	1/0	1/0	1/0	1/0	25
	-	-	-	2	-	-	-	-	1	-	25
WRD259	-	2/0	-	-	2/0	-	2/0	2/0	2/0	2/0	25
	1/0	1/0	-	1/0	1/0	-	1/0	1/0	1/0	1/0	25
	1	-	-	1	-	-	-	-	-	-	25
WRD299	-	3/0	-	-	-	2	3/0	3/0	-	2	25
	2/0	2/0	-	-	3	3	2/0	-	-	3	25
	1/0	-	-	4	4	4	-	-	4	4	25
	-	-	-	6	6	6	-	-	6	6	25
WRD359	-	-	-	-	1/0	-	-	-	-	-	25
	4/0	4/0	-	1	1	1	266	266	1/0	1/0	25
	3/0	3/0	-	2	2	-	-	250	1	1	25
	-	-	-	3	3	-	4/0	4/0	2	2	25
	-	-	-	4	-	-	3/0	-	-	-	25
WRD369	4/0	4/0	-	1/0	1/0	1/0	266	266	1/0	1/0	25
	3/0	3/0	-	1	1	1	-	250	1	1	25
	2/0	-	-	2	2	2	4/0	4/0	2	2	25
	-	-	-	3	3	-	3/0	3/0	3	-	25
	-	-	-	4	4	-	-	-	4	-	25
WRD389	-	-	-	-	-	-	266	266	-	-	25
	4/0	4/0	-	-	3/0	-	-	250	3/0	3/0	25
	3/0	3/0	-	2/0	2/0	-	4/0	4/0	2/0	-	25
	-	-	-	1/0	-	-	3/0	-	-	-	25