

# CONNECTORS

## Compression Connectors

### Long Barrel Copper Lugs Two Hole LN Series




#### SPECIFICATIONS

- UL486A Listed Wire Connector.
- UL467 Grounding & Bonding (Sizes 8 AWG - 3/0 AWG).
- Max ampacity is based on NEC 310.15, insulation type, and conductor material. Please consult your current NEC manual..
- \* CLASS B OR C BUILDING WIRE CU CABLE ONLY.
- Temperature Rating: 90 °C.
- Voltage: 600V.
- 9CU.

#### FEATURES

- Produced from high conductivity copper tubing.
- Allows easy inspection of the termination to assure complete cable insertion.
- Tin-plated to provide corrosion and low contact resistance.
- Marked with die index and color coded.
- Listed for 35KV maximum when properly installed.
- For applications greater than 2000V, installed to cable manufacturer voltage stress relief instructions.
- Part Numbers ending in "P" have a "peep" or sight inspection hole.



**\*EXPANDED WIRE RANGE** when installed with NSI N12ID dieless compression tool.  
UL Listed with other tools:  
**FOR TOOL/DIE CRIMPING INFORMATION, PLEASE SEE TABLE ON PAGE 87**

CAT. NO.	WIRE RANGE	EXPANDED WIRE RANGE*	COLOR	BOLT SIZE (IN.)	MTG. HOLE SPACING (D) (IN.)	BARREL I.D.	BARREL O.D.	LENGTH (L) (IN.)	WIDTH (W)	END OF CONN TO CTR. (A) (IN.)	TANG LENGTH (B) (IN.)	BARREL LENGTH (B1) (IN.)	TANG THICKNESS (C) (IN.)	MTG. HOLE DIA. (E) (IN.)	STD. CTN. QTY.
L8N-14	8 AWG	8 - 10 AWG	Red	1/4"	1.000	0.205	0.295	2.240	0.420	0.280	1.140	0.980	0.080	0.261	100
L8N-14P	8 AWG	8 - 10 AWG	Red	1/4"	1.000	0.205	0.295	2.240	0.420	0.280	1.140	0.980	0.080	0.261	100
L8N-141	8 AWG	8 - 10 AWG	Red	1/4"	0.625	0.205	0.295	2.240	0.420	0.280	1.140	0.980	0.080	0.261	100
L8N-141P	8 AWG	8 - 10 AWG	Red	1/4"	0.625	0.205	0.295	2.240	0.420	0.280	1.140	0.980	0.080	0.261	100
L8N-142	8 AWG	8 - 10 AWG	Red	1/4"	0.750	0.205	0.295	2.240	0.420	0.280	1.140	0.980	0.080	0.261	100
L8N-142P	8 AWG	8 - 10 AWG	Red	1/4"	0.750	0.205	0.295	2.240	0.420	0.280	1.140	0.980	0.080	0.261	100
L8N-563	8 AWG	8 - 10 AWG	Blue	5/16"	1.750	0.205	0.295	2.240	0.420	0.280	1.140	0.980	0.080	0.312	100
L8N-563P	8 AWG	8 - 10 AWG	Blue	5/16"	1.750	0.205	0.295	2.240	0.420	0.280	1.140	0.980	0.080	0.312	100
L6N-12	6 AWG	6 - 8 AWG	Blue	1/4"	0.500	0.200	0.300	2.240	0.420	0.280	1.140	0.980	0.080	0.261	100
L6N-14	6 AWG	6 - 8 AWG	Blue	1/4"	0.625	0.200	0.300	2.360	0.420	0.280	1.260	0.980	0.080	0.261	100
L6N-14P	6 AWG	6 - 8 AWG	Blue	1/4"	0.625	0.200	0.300	2.360	0.420	0.280	1.260	0.980	0.080	0.261	100
L6N-141	6 AWG	6 - 8 AWG	Blue	1/4"	0.625	0.200	0.300	2.480	0.420	1.260	1.380	0.980	0.080	0.261	100
L6N-141P	6 AWG	6 - 8 AWG	Blue	1/4"	0.625	0.200	0.300	2.480	0.420	1.260	1.380	0.980	0.080	0.261	100
L6N-142	6 AWG	6 - 8 AWG	Blue	1/4"	0.750	0.200	0.300	2.480	0.420	0.280	1.380	0.980	0.080	0.261	100
L6N-143	6 AWG	6 - 8 AWG	Blue	1/4"	1.000	0.200	0.300	2.480	0.420	0.280	1.380	0.980	0.080	0.261	100
L6N-142P	6 AWG	6 - 8 AWG	Blue	1/4"	0.750	0.200	0.300	2.480	0.420	0.280	1.380	0.980	0.080	0.261	100
L6N-38	6 AWG	6 - 8 AWG	Blue	3/8"	1.000	0.200	0.300	2.910	0.420	0.380	1.810	0.980	0.080	0.410	100
L6N-38P	6 AWG	6 - 8 AWG	Blue	3/8"	1.000	0.200	0.300	2.910	0.420	0.380	1.810	0.980	0.080	0.410	100
L6N-382	6 AWG	6 - 8 AWG	Blue	3/8"	0.750	0.200	0.300	4.090	0.870	0.620	2.990	0.980	0.120	0.410	100
L6N-382P	6 AWG	6 - 8 AWG	Blue	3/8"	0.750	0.200	0.300	4.090	0.870	0.620	2.990	0.980	0.120	0.410	100
L6N	6 AWG	6 - 8 AWG	Blue	1/2"	1.750	0.200	0.300	4.090	0.870	0.620	2.990	0.980	0.120	0.510	100
L6NP	6 AWG	6 - 8 AWG	Blue	1/2"	1.750	0.200	0.300	4.090	0.870	0.620	2.990	0.980	0.120	0.510	100
L4N-14	4 AWG	4 - 6 AWG	Gray	1/4"	0.625	0.250	0.340	2.360	0.490	0.280	1.260	0.980	0.090	0.261	100

CONNECTORS