

CONNECTORS

Compression Connectors

C-Taps
CT Series



SPECIFICATIONS

- UL486A Listed Wire Connector.
- UL467 Listed Grounding & Bonding.
- * CLASS B OR C BUILDING WIRE CU CABLE ONLY.

FEATURES

- These taps ensure positive, all-around compression with low resistance and high pull-out values.
- Made of high conductivity copper, they satisfy the requirements of NEC250-81 and 250-91 for connecting to the grounding electrode system.
- Rated for 600V applications.

CONNECTORS

**FOR TOOL/DIE CRIMPING INFORMATION,
PLEASE SEE TABLE ON PAGE 88**

CAT. NO.	WIRE SIZE		COLOR CODE	STD. CTN. QTY.
	MAIN	BRANCH		
CT-101	14	16	Red	100
	12	14	Red	100
CT-102	10	10	Blue	100
	8	12	Blue	100
CT-103	6	10-12	Gray	100
	8	8-10	Gray	100
CT-104	4 or 5	8-10-12	Brown	100
	6	6-8	Brown	100
CT-105	—	6-8-10-12	Green	100
	4 or 5	6-5	Green	100
CT-106	—	5	Pink	100
	4	4	Pink	100
CT-107	1	—	Black	50
	2	4-5	Black	50
	3	3-4	Black	50
CT-108	1/0	4	Orange	50
	1	3-4	Orange	50
	2	2-3	Orange	50
CT-109	2/0	3-4	Purple	50
	1/0	2-3	Purple	50
	-	1-2	Purple	50
CT-110	3/0	2-3-4	Yellow	25
	2/0	1-2	Yellow	25
	1/0	1/0-1	Yellow	25