

CONNECTORS

Compression Connectors

C-Taps
CTH Series



SPECIFICATIONS

- UL486A Listed Wire Connector.
- UL467 Listed Grounding & Bonding.
- * CLASS B OR C BUILDING WIRE CU CABLE ONLY.
- Temperature Rating: 90 °C.
- Voltage: 600V.

FEATURES

- These taps ensure positive, all-around compression with low resistance and high pull-out values.
- Made of high conductivity copper, they satisfy the requirements of NEC250 for connecting to the grounding electrode system.
- Rated for 600V applications.

**FOR TOOL/DIE CRIMPING INFORMATION,
PLEASE SEE TABLE ON PAGE 88**

CAT. NO.	WIRE SIZE		COLOR CODE	STD. CTN. QTY.
	MAIN	BRANCH		
CTH-111	1	1	Blue	25
	1/0	1/0-2	Blue	25
	2/0	2/0-4	Blue	25
	3/0	1/0-6	Blue	25
	4/0	1-8	Blue	25
CTH-112	2/0	2/0-1	Brown	25
	3/0	3/0-3	Brown	25
	4/0	4/0-4	Brown	25
	250	1/0-8	Brown	25
CTH-113	2/0	2/0-1	Pink	12
	3/0	3/0-2	Pink	12
	4/0	4/0-4	Pink	12
	250	3/0-6	Pink	12
	300	2/0-8	Pink	12
CTH-114	4/0	4/0-2/0	Black	6
	250	250-1	Black	6
	300	4/0-4	Black	6
	350	3/0-6	Black	6
CTH-115	250	250	Yellow	6
	300	300-3/0	Yellow	6
	350	350-1/0	Yellow	6
	400	300-2	Yellow	6
	450	250-4	Yellow	6
	500	250-6	Yellow	6
CTH-116	350	350-4/0	White	3
	400	400-2/0	White	3
	450	450-1	White	3
	500	500-2	White	3
CTH-117	750-500	4/0-6	-	3
	750	750-4/0	White	3