

# CONNECTORS

## Compression Connectors

Copper "C" Taps  
CTH Series



### SPECIFICATIONS

- UL486A Listed Wire Connector.
- UL467 Listed Grounding & Bonding.
- \* CLASS B OR C BUILDING WIRE CU CABLE ONLY.
- Temperature Rating: 90 °C.
- Voltage: 600V.

### FEATURES

- Range-taking compression connectors made from high conductivity copper alloy.
- Ideal for making tap or parallel copper connections from 8 SOL to 4/0 STR conductors.
- Provides consistent reliability with heavy wall construction that prevents relaxation of the joint after installation.
- Installation time is reduced because of its "C" shape.

**FOR TOOL/DIE CRIMPING INFORMATION,  
PLEASE SEE TABLE ON PAGE 89**

CAT. NO.	CONDUCTOR RANGE		STRIP LENGTH (IN.)	STD. CTN. QTY.
	RUN	TAP		
CTH-46	6 SOL - 4 STR	6 SOL - 6 STR	3/4	25
CTH-44	6 SOL - 4 STR	4 SOL - 4 STR	3/4	25
CTH-24	2 SOL - 2 STR	8 SOL - 4 STR	7/8	10
CTH-22	2 SOL - 2 STR	2 SOL - 2 STR	7/8	25
CTH-2020	1/0 STR - 2/0 STR	1/0 STR - 2/0 STR	11/16	3
CTH-4020	3/0 STR - 4/0 STR	1/0 STR - 2/0 STR	13/16	3
CTH-4040	3/0 STR - 4/0 STR	3/0 STR - 4/0 STR	13/16	3