



IPL600-3 SHOWN

PART NUMBER	NO. OF PORTS	LENGTH
IPL600-3	3	4.47
IPL600-4	4	5.77
IPL600-5	5	7.07
IPL600-6	6	8.37
IPL600-8	8	10.97

WIRE ENTRY PORT
WIRE RANGE: 600 MCM - #6 AWG
PRE-FILLED W/ OXIDE INHIBITOR

CONTACT NSi FOR SALES @ 800.321.5847

NOTES:

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
- DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
- COLD TEMPERATURE RATED TO -45°C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.

		POLARIS SALES CO. INC
<small>PROPRIETARY AND CONFIDENTIAL</small>		<small>11625 PROSPEROUS DRIVE ODESSA, FL 33556</small>
<small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.</small>		TITLE: INSULATED 600 CONNECTOR
<small>DRAWN BY</small> L. HILL	<small>NAME</small> L. HILL	<small>DATE</small> 02/01/2011
<small>MATERIAL:</small> N/A		<small>DWG. NO.</small> IPL600-
<small>SCALE:</small> N/A		<small>SHEET:</small> 1 OF 1