



REMOVABLE CAP
TO TIGHTEN SCREW
(REPLACE WHEN COMPLETE)

REMOVABLE CAP
FOR DUAL ENTRY
(INSERT IN OTHER SIDE)

IPLD750-5 SHOWN

PART NUMBER	NO. OF PORTS	LENGTH
IPLD750-3	3	4.95
IPLD750-4	4	6.38
IPLD750-5	5	7.80
IPLD750-6	6	9.23
IPLD750-7	7	10.65
IPLD750-8	8	12.08
IPLD750-10	10	14.93
IPLD750-12	12	17.78



WIRE ENTRY POINT
WIRE RANGE: 750KCMIL - 250
PRE-FILLED W/ OXIDE INHIBITOR

3/8 INTERNAL HEX PRESSURE SCREW



CONTACT NSI FOR SALES @ 800.321.5847

NOTES:

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
- COLD TEMPERATURE RATED TO -45°C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.

		POLARIS SALES CO. INC	
<small>PROPRIETARY AND CONFIDENTIAL</small>		<small>11625 PROSPEROUS DRIVE ODESSA, FL 33556</small>	
<small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.</small>		TITLE: INSULATED DUAL ENTRY 750 CONNECTOR	
<small>NAME</small>		<small>DATE</small>	
<small>DRAWN BY</small> S.PARRY		<small>DATE</small> 6/2012	
<small>MATERIAL:</small> N/A		<small>DWG. NO.</small> IPLD750-	
<small>SCALE:</small> N/A		<small>SHEET:</small> 1 OF 1	