



REMOVABLE CAP
TO TIGHTEN SCREW
(REPLACE WHEN COMPLETE)

REMOVABLE CAP
FOR DUAL ENTRY
(INSERT IN OTHER SIDE)

5/16 INTERNAL
HEX PRESSURE SCREW



WIRE ENTRY PORT
WIRE RANGE: 350KCMIL - #6 AWG
PRE-FILLED W/ OXIDE INHIBITOR



IPLDS350-10 SHOWN

NSI PART NUMBER	UL PART NUMBER	NO. OF PORTS	LENGTH
IPLDS350-4	IS4E	4	2.55
IPLDS350-6	IS6E	6	3.60
IPLDS350-8	IS8E	8	4.65
IPLDS350-10	IS10E	10	5.70
IPLDS350-12	IS12E	12	6.75
IPLDS350-14	IS14E	14	7.80

CONTACT NSI FOR SALES @ 800.321.5847



POLARIS
SALES CO. INC

PROPRIETARY AND CONFIDENTIAL

11625 PROSPEROUS DRIVE ODESSA, FL 33556

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.

TITLE:
INSULATED STACKED
DUAL ENTRY (BOTTOM ROW)
350 CONNECTOR

NAME DATE
DRAWN BY S.PARRY 06/2012

DWG. NO.
IPLDS350-

MATERIAL: N/A

SCALE: N/A

SHEET: 1 OF 1

NOTES:

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
- DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
- COLD TEMPERATURE RATED TO -45°C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.