



REMOVABLE CAP TO TIGHTEN SCREW (REPLACE WHEN COMPLETE)

INSULATED MOUNTING PORT ON EACH END FOR 1/4 BOLT

WIRE ENTRY POINT
WIRE RANGE: #4 - #14 AWG
PRE-FILLED W/ OXIDE INHIBITOR

SLOTTED PRESSURE SCREWS

CONTACT NSI FOR SALES @ 800.321.5847

IPLM4-4 SHOWN

PART NUMBER	NO. OF PORTS	LENGTH
IPLM4-3	3	2.75
IPLM4-4	4	3.18
IPLM4-5	5	3.60
IPLM4-6	6	4.02
IPLM4-7	7	4.19
IPLM4-8	8	4.86
IPLM4-10	10	5.71
IPLM4-12	12	6.30

NOTES:

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
- DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
- COLD TEMPERATURE RATED TO -45°C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.

		POLARIS SALES CO. INC	
PROPRIETARY AND CONFIDENTIAL		11625 PROSPEROUS DRIVE ODESSA, FL 33556	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.		TITLE: INSULATED MOUNTED #4 CONNECTOR	
DWG. NO. IPLM4-		SCALE: N/A	
NAME S.PARRY	DATE 06/2012	SHEET: 1 OF 1	
MATERIAL: N/A		SCALE: N/A	