





REMOVABLE CAP  
TO TIGHTEN SCREW  
(REPLACE WHEN COMPLETE)

REMOVABLE CAP  
FOR DUAL ENTRY  
(INSERT IN OTHER SIDE)

IPLMD500-5 SHOWN

PART NUMBER	NO. OF PORTS	LENGTH
IPLMD500-3	3	5.51
IPLMD500-4	4	6.65
IPLMD500-5	5	7.80
IPLMD500-6	6	8.94
IPLMD500-7	7	9.71
IPLMD500-8	8	11.23
IPLMD500-10	10	13.52
IPLMD500-12	12	15.44

WIRE ENTRY POINT  
WIRE RANGE: 500KCMIL - #4AWG  
PRE-FILLED W/ OXIDE INHIBITOR



CONTACT NSI FOR SALES @ 800.321.5847



**POLARIS**  
SALES . CO . INC

PROPRIETARY AND CONFIDENTIAL

11625 PROSPEROUS DRIVE ODESSA, FL 33556

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.

**TITLE:**  
INSULATED MOUNTED  
DUAL ENTRY  
500 CONNECTOR

NAME	DATE
DRAWN BY S.PARRY	06/2012

**DWG. NO.**  
IPLMD500-

**MATERIAL:** N/A

**SCALE:** N/A

**SHEET:** 1 OF 1

**NOTES:**

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
- DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
- COLD TEMPERATURE RATED TO -45°C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.