




REMOVABLE CAP
TO TIGHTEN SCREW
(REPLACE WHEN COMPLETE)

REMOVABLE CAP
FOR DUAL ENTRY
(INSERT IN OTHER SIDE)

IPLMD750-5 SHOWN

PART NUMBER	NO. OF PORTS	LENGTH
IPLMD750-3	3	6.32
IPLMD750-4	4	7.75
IPLMD750-5	5	9.18
IPLMD750-6	6	10.60
IPLMD750-7	7	11.65
IPLMD750-8	8	13.45
IPLMD750-10	10	16.30
IPLMD750-12	12	18.78

WIRE ENTRY POINT
WIRE RANGE: 750KCMIL - 250
PRE-FILLED W/ OXIDE INHIBITOR



INSULATED MOUNTING PORT ON EACH END
FOR A 5/16 BOLT



5/16 INTERNAL HEX PRESSURE SCREW

CONTACT NSI FOR SALES @ 800.321.5847



POLARIS
SALES CO. INC

PROPRIETARY AND CONFIDENTIAL

11625 PROSPEROUS DRIVE ODESSA, FL 33556

THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
POLARIS SALES CO. INC. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
POLARIS SALES CO. INC. IS PROHIBITED.

TITLE:

INSULATED MOUNTED
DUAL ENTRY
750 CONNECTOR

NAME	DATE
S.PARRY	06/2012

DWG. NO.

IPLMD750-

MATERIAL: N/A

SCALE: N/A

SHEET: 1 OF 1

NOTES:

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- DUAL RATED FOR 90 °C COPPER AND/OR ALUMINUM CONDUCTOR.
- COLD TEMPERATURE RATED TO -45 °C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.