


Nylon Insulated Ring Terminals

Drawn - SD

Approved - KM

Material - Copper / Nylon Insulation

Title - Nylon Insulated Ring Terminals



Part Number	Wire Range	Insulated Color	Electrical Rating Max	d2	B	F	L	E	D	d1
R22-4N	22-18 AWG	RED	105C / 600 Volts	0.140	0.255	0.258	0.910	0.533	0.208	0.160
R22-6N	22-18 AWG	RED	105C / 600 Volts	0.146	0.315	0.276	0.866	0.433	0.161	0.067
R22-8N	22-18 AWG	RED	105C / 600 Volts	0.169	0.315	0.276	0.866	0.433	0.161	0.067
R22-10N	22-18 AWG	RED	105C / 600 Volts	0.209	0.315	0.276	0.866	0.433	0.161	0.067
R22-14N	22-18 AWG	RED	105C / 600 Volts	0.256	0.457	0.437	1.094	0.433	0.161	0.067
R22-56N	22-18 AWG	RED	105C / 600 Volts	0.331	0.457	0.437	1.094	0.433	0.161	0.067
R22-38N	22-18 AWG	RED	105C / 600 Volts	0.413	0.535	0.547	1.248	0.433	0.161	0.067
R16-6N	16-14 AWG	BLUE	105C / 600 Volts	0.140	0.312	0.310	0.973	0.540	0.235	0.182
R16-8N	16-14 AWG	BLUE	105C / 600 Volts	0.169	0.335	0.307	0.906	0.433	0.177	0.091
R16-10N	16-14 AWG	BLUE	105C / 600 Volts	0.209	0.335	0.307	0.906	0.433	0.177	0.091
R16-14N	16-14 AWG	BLUE	105C / 600 Volts	0.256	0.472	0.433	1.102	0.433	0.177	0.091
R16-56N	16-14 AWG	BLUE	105C / 600 Volts	0.146	0.260	0.248	0.807	0.433	0.177	0.091
R16-38N	16-14 AWG	BLUE	105C / 600 Volts	0.413	0.535	0.547	1.248	0.433	0.177	0.091
R16-50N	16-14 AWG	BLUE	105C / 600 Volts	0.512	0.756	0.630	1.441	0.433	0.177	0.091
R12-6N	12-10 AWG	YELLOW	105C / 600 Volts	0.146	0.374	0.327	1.024	0.512	0.256	0.134
R12-8N	12-10 AWG	YELLOW	105C / 600 Volts	0.169	0.374	0.327	1.024	0.512	0.256	0.134
R12-10N	12-10 AWG	YELLOW	105C / 600 Volts	0.209	0.374	0.327	1.024	0.512	0.256	0.134
R12-14N	12-10 AWG	YELLOW	105C / 600 Volts	0.256	0.472	0.413	1.161	0.512	0.256	0.134
R12-56N	12-10 AWG	YELLOW	105C / 600 Volts	0.331	0.591	0.539	1.346	0.512	0.256	0.134
R12-38N	12-10 AWG	YELLOW	105C / 600 Volts	0.413	0.591	0.539	1.346	0.512	0.256	0.134
R12-50N	12-10 AWG	YELLOW	105C / 600 Volts	0.512	0.756	0.630	1.520	0.512	0.256	0.134
R8-10N	8 AWG	RED	105C / 600 Volts	0.190	0.469	0.430	1.354	0.736	0.410	0.114
R8-14N	8 AWG	RED	105C / 600 Volts	0.263	0.463	0.440	1.354	0.736	0.410	0.114
R8-56N	8 AWG	RED	105C / 600 Volts	0.324	0.467	0.435	1.361	0.745	0.420	0.187
R8-38N	8 AWG	RED	105C / 600 Volts	0.389	0.580	0.500	1.480	0.737	0.420	0.187
R6-14N	6 AWG	BLUE	105C / 600 Volts	0.265	0.472	0.550	1.577	0.813	0.488	0.250
R6-56N	6 AWG	BLUE	105C / 600 Volts	0.330	0.625	0.550	1.660	0.820	0.490	0.430
R6-38N	6 AWG	BLUE	105C / 600 Volts	0.392	0.633	0.550	1.660	0.820	0.490	0.430
R6-50N	6 AWG	BLUE	105C / 600 Volts	0.520	0.867	0.785	1.990	0.839	0.510	0.430
R4-14N	4 AWG	YELLOW	105C / 600 Volts	0.266	0.482	0.590	1.767	1.027	0.580	0.507
R4-56N	4 AWG	YELLOW	105C / 600 Volts	0.325	0.478	0.584	1.752	1.020	0.580	0.507
R4-38N	4 AWG	YELLOW	105C / 600 Volts	0.390	0.667	0.630	1.886	1.013	0.579	0.507
R4-50N	4 AWG	YELLOW	105C / 600 Volts	0.520	0.667	0.630	1.886	1.013	0.579	0.507
R2-14N	2 AWG	RED	105C / 600 Volts	0.264	0.634	0.770	2.142	1.110	0.693	0.605
R2-56N	2 AWG	RED	105C / 600 Volts	0.325	0.633	0.760	2.213	1.102	0.692	0.590
R2-38N	2 AWG	RED	105C / 600 Volts	0.390	0.634	0.756	2.118	1.126	0.689	0.610
R2-50N	2 AWG	RED	105C / 600 Volts	0.515	0.634	0.756	2.142	1.126	0.689	0.610